

Fire ratings are available in most JELD-WEN® Door product lines. There may be restrictions based on size and regional availability, so please use this sheet as a reference and discuss further with your JELD-WEN supplier. All door slabs must be used with fire-rated door systems for true fire protection. A door system consists of the door slab, frame, hardware and components.

Exterior Doors				
Product Type	Ratings	Models	Largest Slab Size	
IWP® Custom Wood Doors	20-Minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" to 2-1/4" doors Available with all-panel doors Radius top doors up to 60-Minutes Segment top doors up to 90-Minutes Select 20- and 45-Minute doors available with glass (Custom quoted)	4'0" x 8'0" Single* 7'0" x 8'0" Pair*	
	45-Minutes			<ul style="list-style-type: none"> • FyreWerks® core • 1-3/4" to 2-1/4" doors
	60-Minutes			<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors
	90-Minutes			<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors
Fiberglass Doors	20-Minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" doors • Laminated Veneer Lumber (LVL) or wood stiles & rails • LFI-capped top rail and PVC-capped stiles and bottom rails Available with all-panel doors Architectural™ Fiberglass Doors Design-Pro™ Fiberglass Doors Smooth-Pro™ Fiberglass Doors	3'0" x 8'0" Single 6'0" x 6'8" Pair	
Steel Doors	20-Minutes	<ul style="list-style-type: none"> • Wood edge • Steel edge Available with Contours™ all-panel doors	3'0" x 6'8" Single 3'0" x 8'0" Single 6'0" x 7'0" Pair 3'6" x 7'0" Single	
	20-, 45-, 60- and 90-Minutes			
IWP® Aurora® Custom Fiberglass doors	20-Minutes	Available in all-panel designs. Arch tops approved.	3'0" x 8'0" Single	
Interior Doors				
Product Type	Ratings	Models	Largest Slab Size	
Custom Wood Doors	20-Minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" to 2-1/4" doors Available with all-panel doors Radius top doors up to 60-Minutes Segment top doors up to 90-Minutes Select 20- and 45-Minute doors available with glass (Custom quoted)	4'0" x 8'0" Single* 7'0" x 8'0" Pair*	
	45-Minutes			<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors
	60-Minutes			<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors
	90-Minutes			<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors
Custom Carved Doors	20-Minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" doors Available with all raised panel doors Available in recessed panel doors with largest slab size of 3'0" x 6'8"	3'0" x 8'0" Single 6'0" x 8'0" Pair	
Molded Doors	20-Minutes	<ul style="list-style-type: none"> • Wood-based panel core • 1-3/4" doors Available in all standard models except Impression™ Series doors Craftsman III™ Smooth, Madison™ Smooth and Conmore® Smooth doors available with 20-Minute Fire rating for 3'0" x 8'0" maximum size	3'0" x 8'0" Single 6'0" x 8'0" Pair 3'6" x 7'0" Single 3'0" x 8'0" Single 6'0" x 8'0" Pair	
	45-Minutes			<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors
	60-Minutes			<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors
Flush Doors	20-Minutes	<ul style="list-style-type: none"> • Wood-based panel core • 1-3/4" doors Available in all models Glass available up to 1,296 square inches, depending on fire rating	4'0" x 10'0" Single 8'0" x 10'0" Pair 4'0" x 9'0" Single 8'0" x 9'0" Pair	
	45-Minutes			<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors
	60-Minutes			<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors
	90-Minutes			<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors

*Size limitations for IWP Custom Wood fire-rated doors in fire-rated wood jamb: 20-Minutes: 3'6" x 8'0" single, 5'6" x 8'0" pair; 45/60/90-Minutes: 3'6" x 8'0" single