

Acoustic Ratings - Exterior Doors

Key

L = Laminated

STC = Sound Transmission Class (ASTM E413)

OITC = Outdoor/Indoor Transmission Class (ASTM E1332)

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

Aurora® Custom Fiberglass

	<u> </u>	
Туре	STC	ОІТС
Glazed*	31	27
Glazed* Impact	35	30
Opaque	26	25

Contours[™] Steel, Steel Edge

Туре	STC	OITC
Glazed*	28	25
Opaque	22	22

Contours[™] Steel, Wood Edge

Туре	STC	ОІТС
Glazed*	27	25
Opaque	20	22

$\textbf{Design-Pro}^{\text{TM}} \textbf{ and Smooth-Pro}^{\text{TM}} \textbf{ Fiberglass}$

Туре	STC	OITC
20 min Fire Door	29	28
Glazed*	27	22
Flush Glazed*	27	23
Opaque	24	22

Finishield® and Gladiator® Steel, Wood Edge

Туре	STC	ОІТС
Glazed*	26	25
Opaque	19	21

^{*} Glazed Door values are applicable to all door lite configurations