

**Key**

L = Laminated

STC = Sound Transmission Class (ASTM E413)

OITC = Outdoor/Indoor Transmission Class (ASTM E1332)

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

Molded Wood Composite Interior Doors		
Type	STC	OITC
Avalon ProCore	32	29
Avalon Hollow Core	26	22
Colonist Textured ProCore (6 panel)	30	28
Colonist Textured Hollow Core	26	19
Colonial 60 min. Fire Rated Door (6 panel)	29	29
Colonial 20 min. Fire Rated Door (6 panel)	30	29
Colonial Hollow Core (6 panel)	25	20
Colonial Procore (6 panel)	30	29
Coventry Smooth	30	28
Coventry Smooth Hollow Core	26	19
Caiman Smooth ProCore	30	29
Caiman Smooth Hollow Core	27	21
Camden ProCore	30	29
Camden Hollow Core	27	21
Cambridge ProCore	30	29
Cambridge Hollow Core	27	21
Carrara Smooth ProCore	30	29
Carrara Smooth Hollow Core	27	21
Cashal Smooth ProCore	30	29
Cashal Smooth Hollow Core	27	21
Conmore Smooth ProCore	30	28
Conmore Smooth Hollow Core	25	20
Continental Smooth ProCore	30	29
Continental Smooth Hollow Core	27	21
Corvado Smooth ProCore	30	29
Corvado Smooth Hollow Core	27	21
Craftsman III ProCore	30	28
Craftsman III Hollow Core	25	20
Madison ProCore	32	29
Madison Hollow Core	26	22
Princeton ProCore	30	29
Princeton Hollow Core	27	21
Provincial ProCore	30	28
Provincial Hollow Core	26	19
RockPort ProCore	30	28
RockPort Hollow Core	25	20
Santa Fe ProCore	30	29
Santa Fe Hollow Core	27	21
Flush Wood Composite Interior Doors		
Type	STC	OITC
Flush Hollow Core	24	19
Flush Procore	30	29
Flush 20 min. Fire Rated Door	32	30
Flush 60 min. Fire Rated Door	34	31
TRIA Interior Doors		
Type	STC	OITC
C Series 45 min. Fire Rated Door, Seal Set D	36	34
C Series 20 min. Fire Rated Door	36	33
C Series, foam core	27	27
L Series 90 min. Fire Rated Door, Seal Set E	37	33
L Series, Seal Set F, White Laminated	34	31
L Series, Flat Panel 20 min	31	29
R Series 20 min. Fire Rated Door	34	32
R Series, Seal Set A, 20-min RigiCore GP	43	37
<b>Revised 6/12/16</b>		