



KEY

STC = Sound Transmission Class
(ASTM E413)

OITC = Outdoor/Indoor Transmission Class
(ASTM E1332)

The performance information listed is for new products and is intended to be used for reference only. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

| Aurora® Custom Fiberglass | | |
|--|-----|------|
| Type | STC | OITC |
| Glazed* | 31 | 27 |
| Glazed* Impact | 35 | 30 |
| Opaque | 26 | 25 |
| Contours, Energy Saver Steel (Steel Edge) | | |
| Type | STC | OITC |
| Glazed* | 28 | 25 |
| Opaque | 22 | 22 |
| Contours, Energy Saver Steel (Wood Edge) | | |
| Type | STC | OITC |
| Glazed* | 27 | 25 |
| Opaque | 20 | 22 |
| Design-Pro & Smooth-Pro Fiberglass | | |
| Type | STC | OITC |
| 20 min Fire Door | 31 | 29 |
| Glazed* | 30 | 26 |
| Opaque | 25 | 22 |
| Gladiator Steel (Wood Edge) | | |
| Type | STC | OITC |
| Glazed* | 26 | 25 |
| Opaque | 19 | 21 |

* Glazed Door values are applicable to all door lite configurations.