



NEEDED MATERIALS

Needed Materials*

- Bucket
- Simple Green®
- Microfiber cloth
- Lint-free drying cloth
- 3M® ScotchBlue™ Painter's Exterior Surfaces 2097 Tape or FROGTAPE® Delicate Surface Painter's Tape with PaintBlock® Technology



LIGHT COMMERCIAL CARE AND MAINTENANCE OF EVERTONE™ SURFACES

Window and Patio Door Storage and Handling

- If the products must be stored before installation, store in a dry, well-ventilated area off of the floor. Do not remove paper and/or cardboard shipped between products during storage. Buildings where humidity and temperature are controlled provide the best storage facilities (recommended conditions 30%-50% relative humidity and 50°F to 90°F).
- Store products at a slight slant against a wall with the full width of the window or patio door head and sill supported. Allow sufficient space between products for ventilation.
- Protect from exposure to direct sunlight during storage.
- Windows and patio doors should be handled with clean hands and equipment.
- Lift and carry the products to move, do not drag across one another.
- Install only into vertical walls and when conditions are dry.

Cleaning

For residue we recommend that you use Simple Green® to clean the surface of the vinyl product.

Note: Do not use gasoline, diesel fuel, solvent-based, petroleum-based products or abrasive materials to clean EverTone surfaces. Methanol, ethanol and isopropanol type cleaners are not recommended.

1. Simple Green recommends to pre-wet area prior to applying cleaning solution, this will help penetrate the soiled surfaces.
2. To clean painted surface spray Simple Green onto Microfiber cloth, and wipe the soiled area starting at the top of the window working your way down. This process must be repeated if contaminants still persist.
Note! Quickly rinse and dry any run-down. Don't allow cleaning solution to collect or puddle on vinyl surfaces, crevices, etc.
3. Promptly rinse thoroughly with clean water (sponging while rinsing may be helpful).
4. Wipe dry with lint-free, drying cloth.
5. If necessary, repeat steps above until the surfaces are free of contaminants.

How to Touch-up Scratches

Our process produces a finish that is hard and durable and will resist scratching. If scratches occur, a small touch-up paint applicator is included with every EverTone shipment.

1. Shake applicator for 60 seconds.
2. Remove cap.
3. Use the applicator brush tip of the applicator to apply touch-up paint. Deep scratches may require two coats.
4. Let repainted surface dry thoroughly.
5. Polish with a microfiber cloth.

Masonry Facade, Brick or Rock Face Exteriors

For windows and patio doors installed in one of these exterior applications we recommend the product be masked and fully protected from masonry cleaning solutions and excessive sealants. **Note! Do not allow acid wash on any surface of the product.**

When masking the product we recommend 3M® ScotchBlue™ Painter's Exterior Surfaces 2097 Tape or FROGTAPE® Delicate Surface Painter's Tape with PaintBlock® Technology to ensure clean removal of the tape for damage free results. The tape should be removed within 3 weeks of application.

Stucco Exteriors

We recommend 3M® ScotchBlue™ Painter's Exterior Surfaces 2097 Tape or FROGTAPE® Delicate Surface Painter's Tape with PaintBlock® Technology be used to cover the window or patio door surface prior to protecting the product with heavy mil plastic using red tape. Secure the red tape to the ScotchBlue™ Tape or FROGTAPE® for damage free results. The tape should be removed as soon as possible or no longer than 3 weeks of application.

Note: It is the responsibility of the owner, architect or general contractor to select products in compliance with applicable laws and building codes.

*For additional touch-up paint contact JELD-WEN Warranty Group at 1-888-594-3578 or email JWWarranty@jeld-wen.com.

The advice offered herein can be accomplished by a property owner with some mechanical aptitude. If you are unsure, it is recommended that you hire a trained service provider such as a competent and licensed construction contractor or building professional. JELD-WEN disclaims any and all liability associated with the use and/or provision of these instructions. Any reliance upon the information or advice is at the risk of the party so relying. The information contained herein may be changed from time to time without notification.