
ELEVATIONS TABLE OF CONTENTS

Operating Units	1-17
Fixed Units	1-24
2-Wide Units	1-29
3-Wide Units	1-31

OPERATING ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

27 1/4"(692)
30 5/16"(770)
24 3/4"(629)
24"(610)
15 9/16"(395)

31 1/4"(794)
34 5/16"(872)
28 3/4"(730)
28"(711)
19 9/16"(497)


33 1/4"(845)
36 5/16"(922)
30 3/4"(781)
30"(762)
21 9/16"(547)

35 1/4"(895)
38 5/16"(973)
32 3/4"(832)
32"(813)
23 9/16"(598)


39 1/4"(997)
42 5/16"(1075)
36 3/4"(933)
36"(914)
27 9/16"(700)

43 1/4"(1099)
46 5/16"(1176)
40 3/4"(1035)
40"(1016)
31 9/16"(802)


22 1/2"(572)
24 1/16"(611)
20 3/4"(527)
20"(508)
11 9/16"(294)



CCTTH2420



CCTTH2820



CCTTH3020



CCTTH3220




CCTTH3620




CCTTH4020


26 1/2"(673)
28 1/16"(713)
24 3/4"(629)
24"(610)
15 9/16"(395)



CCTTH2424



CCTTH2824



CCTTH3024



CCTTH3224




CCTTH3624




CCTTH4024


31 1/4"(794)
34 5/16"(872)
28 3/4"(730)
28"(711)
19 9/16"(497)




CCTTH2428




CCTTH2828



CCTTH3028



CCTTH3228




CCTTH3628




CCTTH4028


32 1/2"(826)
34 1/16"(865)
30 3/4"(781)
30"(762)
21 9/16"(547)




CCTTH2430




CCTTH2830



CCTTH3030



CCTTH3230




CCTTH3630




CCTTH4030


34 1/2"(876)
36 1/16"(916)
32 3/4"(832)
32"(813)
23 9/16"(598)




CCTTH2432




CCTTH2832



CCTTH3032



CCTTH3232




CCTTH3632




CCTTH4032


38 1/2"(978)
40 1/16"(1018)
36 3/4"(933)
36"(914)
27 9/16"(700)




CCTTH2436




CCTTH2836



CCTTH3036



CCTTH3236




CCTTH3636




CCTTH4036


42 1/2"(1080)
44 1/16"(1119)
40 3/4"(1035)
40"(1016)
31 9/16"(802)




CCTTH2440




CCTTH2840



CCTTH3040



CCTTH3240




CCTTH3640




CCTTH4040


44 1/2"(1130)
46 1/16"(1170)
42 3/4"(1086)
42"(1067)
33 9/16"(852)




CCTTH2442




CCTTH2842



CCTTH3042



CCTTH3242



CCTTH3642



CCTTH4042

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masorny Opening) for Unit Sizes. Masorny openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masorny Openings page.

OPERATING ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

27 1/4"(692)
30 5/16"(770)
24 3/4"(629)
24"(610)
15 9/16"(395)

31 1/4"(794)
34 5/16"(872)
28 3/4"(730)
28"(711)
19 9/16"(497)


33 1/4"(845)
36 5/16"(922)
30 3/4"(781)
30"(762)
21 9/16"(547)

35 1/4"(895)
38 5/16"(973)
32 3/4"(832)
32"(813)
23 9/16"(598)


39 1/4"(997)
42 5/16"(1075)
36 3/4"(933)
36"(914)
27 9/16"(700)

43 1/4"(1099)
46 5/16"(1176)
40 3/4"(1035)
40"(1016)
31 9/16"(802)


50 1/2"(1283)
52 1/16"(1322)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)




CCTTH2448




CCTTH2848




CCTTH3048



CCTTH3248



CCTTH3648



CCTTH4048

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

45 1/4"(1149)
48 5/16"(1227)
42 3/4"(1086)
42"(1067)
33 9/16"(852)

51 1/4"(1302)
54 5/16"(1380)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)

56 1/2"(1435)
58 1/16"(1475)
54 3/4"(1391)
54"(1372)
45 9/16"(1157)

58 1/2"(1486)
60 1/16"(1526)
56 3/4"(1441)
56"(1422)
47 9/16"(1208)

22 1/2"(572)
24 1/16"(611)
20 3/4"(527)
20"(508)
11 9/16"(294)




CCTTH4220

26 1/2"(673)
28 1/16"(713)
24 3/4"(629)
24"(610)
15 9/16"(395)




CCTTH4224

31 1/4"(794)
34 5/16"(872)
28 3/4"(730)
28"(711)
19 9/16"(497)




CCTTH4228

32 1/2"(826)
34 1/16"(865)
30 3/4"(781)
30"(762)
21 9/16"(547)




CCTTH4230

34 1/2"(876)
36 1/16"(916)
32 3/4"(832)
32"(813)
23 9/16"(598)




CCTTH4232

38 1/2"(978)
40 1/16"(1018)
36 3/4"(933)
36"(914)
27 9/16"(700)




CCTTH4236

42 1/2"(1080)
44 1/16"(1119)
40 3/4"(1035)
40"(1016)
31 9/16"(802)



CCTTH4240

44 1/2"(1130)
46 1/16"(1170)
42 3/4"(1086)
42"(1067)
33 9/16"(852)



CCTTH4242



CCTTH4820



CCTTH4824



CCTTH4828




CCTTH4830




CCTTH4832



CCTTH4836



CCTTH4840



CCTTH4842



CCTTH5420



CCTTH5424




CCTTH5428




CCTTH5430




CCTTH5432



CCTTH5436



CCTTH5440



CCTTH5442



CCTTH5620



CCTTH5624




CCTTH5628




CCTTH5630




CCTTH5632



CCTTH5636



CCTTH5640



CCTTH5642

ELEVATION SYMBOL LEGEND:

M.O. = MASORY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O. (Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING


45 1/4"(1149)
48 5/16"(1227)
42 3/4"(1086)
42"(1067)
33 9/16"(852)

51 1/4"(1302)
54 5/16"(1380)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)


56 1/2"(1435)
58 1/16"(1475)
54 3/4"(1391)
54"(1372)
45 9/16"(1157)

58 1/2"(1486)
60 1/16"(1526)
56 3/4"(1441)
56"(1422)
47 9/16"(1208)


50 1/2"(1283)
52 1/16"(1322)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)




CCTTH4248



CCTTH4848



CCTTH5448



CCTTH5648

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O. (Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING ELEVATIONS


MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

62 1/2"(1588)
64 1/16"(1627)
60 3/4"(1543)
60"(1524)
51 9/16"(1310)


66 1/2"(1689)
68 1/16"(1729)
64 3/4"(1645)
64"(1626)
55 9/16"(1411)

70 1/2"(1791)
72 1/16"(1830)
68 3/4"(1746)
68"(1727)
59 9/16"(1513)

22 1/2"(572)
24 1/16"(611)
20 3/4"(527)
20"(508)
11 9/16"(294)



CCTTH6020



CCTTH6420



CCTTH6620

26 1/2"(672)
28 1/16"(713)
24 3/4"(629)
24"(610)
15 9/16"(395)



CCTTH6024



CCTTH6424



CCTTH6624

31 1/4"(794)
34 5/16"(872)
28 3/4"(730)
28 7/11"
19 9/16"(487)



CCTTH6028



CCTTH6428



CCTTH6628

32 1/2"(826)
34 1/16"(865)
30 3/4"(781)
30"(762)
21 9/16"(547)



CCTTH6030



CCTTH6430



CCTTH6630

34 1/2"(876)
36 1/16"(916)
32 3/4"(832)
32"(813)
23 9/16"(608)



CCTTH6032



CCTTH6432



CCTTH6632

38 1/2"(978)
40 1/16"(1018)
36 3/4"(934)
36"(914)
27 9/16"(700)



CCTTH6036



CCTTH6436



CCTTH6636

42 1/2"(1080)
44 1/16"(1119)
40 3/4"(1035)
40"(1016)
31 9/16"(802)



CCTTH6040




CCTTH6440



CCTTH6640

44 1/2"(1130)
46 1/16"(1170)
42 3/4"(1086)
42"(1067)
33 9/16"(862)



CCTTH6042



CCTTH6442



CCTTH6642

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O. (Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING ELEVATIONS


MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

62 1/2"(1588)
64 1/16"(1627)
60 3/4"(1543)
60"(1524)
51 9/16"(1310)


66 1/2"(1689)
68 1/16"(1729)
64 3/4"(1645)
64"(1626)
55 9/16"(1411)

70 1/2"(1791)
72 1/16"(1830)
68 3/4"(1746)
68"(1727)
59 9/16"(1513)


50 1/2"(1283)
52 1/16"(1322)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)



CCTTH6048



CCTTH6448



CCTTH6648

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O. (Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING


74 1/2"(1892)
76 1/16"(1932)
72 3/4"(1848)
72"(1829)
63 9/16"(1614)

22 1/2"(572)
24 1/16"(611)
20 3/4"(527)
20"(508)
11 9/16"(294)



CCTTH7220

26 1/2"(673)
28 1/16"(713)
24 3/4"(629)
24"(610)
15 9/16"(398)



CCTTH7224

31 1/4"(794)
34 5/16"(872)
28 3/4"(730)
28"(711)
19 9/16"(497)



CCTTH7228

32 1/2"(826)
34 1/16"(865)
30 3/4"(781)
30"(762)
21 9/16"(547)




CCTTH7230

34 1/2"(876)
36 1/16"(916)
32 3/4"(832)
32"(813)
23 9/16"(598)



CCTTH7232

38 1/2"(978)
40 1/16"(1018)
36 3/4"(933)
36"(914)
27 9/16"(700)



CCTTH7236

42 1/2"(1080)
44 1/16"(1119)
40 3/4"(1035)
40"(1016)
31 9/16"(802)



CCTTH7240

44 1/2"(1130)
46 1/16"(1170)
42 3/4"(1086)
42"(1067)
33 9/16"(852)




CCTTH7242

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

74 1/2"(1892)
76 1/16"(1932)
72 3/4"(1848)
72"(1829)
63 9/16"(1614)

50 1/2"(1283)
52 1/16"(1322)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)



CCTTH7248

ELEVATION SYMBOL LEGEND:

M.O. = MASONRY OPENING

VALUES IN () ARE IN MILLIMETER CONVERSIONS

NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

43 1/4"(1099)
46 5/16"(1118)
40 3/4"(1035)
40"(1016)
31 9/16"(802)


45 1/4"(1149)
48 5/16"(1227)
42 3/4"(1086)
42"(1067)
33 9/16"(852)

51 1/4"(1302)
54 5/16"(1380)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)


57 1/4"(1454)
60 5/16"(1532)
54 3/4"(1391)
54"(1372)
45 9/16"(1157)

59 1/4"(1505)
62 5/16"(1583)
56 3/4"(1441)
56"(1422)
47 9/16"(1208)


20 1/2"(621)
22 1/16"(660)
18 3/4"(476)
18"(457)
9 9/16"(243)




CCTTHP4018




CCTTHP4218



CCTTHP4818



CCTTHP5418



CCTTHP5618

22 1/2"(672)
24 1/16"(611)
20 3/4"(527)
20"(508)
11 9/16"(294)



CCTTHP4020



CCTTHP4220



CCTTHP4820




CCTTHP5420




CCTTHP5620

26 1/2"(673)
28 1/16"(713)
24 3/4"(629)
24"(610)
15 9/16"(395)




CCTTHP4024



CCTTHP4224



CCTTHP4824



CCTTHP5424



CCTTHP5624

32 1/2"(826)
34 1/16"(865)
30 3/4"(781)
30"(762)
21 9/16"(547)



CCTTHP4030



CCTTHP4230



CCTTHP4830




CCTTHP5430



CCTTHP5630


34 1/2"(876)
36 1/16"(916)
32 3/4"(832)
32"(813)
23 9/16"(598)



CCTTHP4032



CCTTHP4232



CCTTHP4832



CCTTHP5432



CCTTHP5632


38 1/2"(978)
40 1/16"(1018)
36 3/4"(933)
36"(914)
27 9/16"(700)



CCTTHP4036



CCTTHP4236



CCTTHP4836



CCTTHP5436



CCTTHP5636

42 1/2"(1080)
44 1/16"(1119)
40 3/4"(1035)
40"(1016)
31 9/16"(802)



CCTTHP4040



CCTTHP4240



CCTTHP4840



CCTTHP5440



CCTTHP5640

44 1/2"(1130)
46 1/16"(1170)
42 3/4"(1086)
42"(1067)
33 9/16"(852)



CCTTHP4042



CCTTHP4242



CCTTHP4842



CCTTHP5442



CCTTHP5642

ELEVATION SYMBOL LEGEND:

M.O. = MASONRY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

43 1/4"(1099)
46 5/16"(1118)
40 3/4"(1035)
40"(1016)
31 9/16"(802)


45 1/4"(1149)
48 5/16"(1227)
42 3/4"(1086)
42"(1067)
33 9/16"(852)

51 1/4"(1302)
54 5/16"(1380)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)


57 1/4"(1454)
60 5/16"(1532)
54 3/4"(1391)
54"(1372)
45 9/16"(1157)

59 1/4"(1505)
62 5/16"(1583)
56 3/4"(1441)
56"(1422)
47 9/16"(1208)


50 1/2"(1283)
52 1/16"(1322)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)




CCTTHP4048




CCTTHP4248



CCTTHP4848




CCTTHP5448




CCTTHP5648


56 1/2"(1435)
58 1/16"(1475)
54 3/4"(1391)
54"(1372)
45 9/16"(1157)




CCTTHP4054




CCTTHP4254



CCTTHP4854




CCTTHP5454




CCTTHP5654


58 1/2"(1486)
60 1/16"(1526)
56 3/4"(1441)
56"(1422)
47 9/16"(1208)




CCTTHP4056




CCTTHP4256



CCTTHP4856




CCTTHP5456




CCTTHP5656


62 1/2"(1588)
64 1/16"(1627)
60 3/4"(1543)
60"(1524)
51 9/16"(1310)




CCTTHP4060




CCTTHP4260



CCTTHP4860




CCTTHP5460




CCTTHP5660


66 1/2"(1689)
68 1/16"(1729)
64 3/4"(1645)
64"(1626)
55 9/16"(1411)




CCTTHP4064




CCTTHP4264



CCTTHP4864



CCTTHP5464



CCTTHP5664

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O. (Masorny Opening) for Unit Sizes. Masorny openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masorny Openings page.

FIXED UNIT ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

43 1/4"(1099)
46 5/16"(1118)
40 3/4"(1035)
40"(1016)
31 9/16"(802)


45 1/4"(1149)
48 5/16"(1227)
42 3/4"(1086)
42"(1067)
33 9/16"(852)

51 1/4"(1302)
54 5/16"(1380)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)


57 1/4"(1454)
60 5/16"(1532)
54 3/4"(1391)
54"(1372)
45 9/16"(1157)

59 1/4"(1505)
62 5/16"(1583)
56 3/4"(1441)
56"(1422)
47 9/16"(1208)


68 1/2"(1740)
70 1/16"(1780)
66 3/4"(1695)
66"(1676)
57 9/16"(1462)




CCTTHP4066




CCTTHP4266



CCTTHP4866




CCTTHP5466




CCTTHP5666


74 1/2"(1892)
76 1/16"(1932)
72 3/4"(1848)
72"(1829)
63 9/16"(1614)




CCTTHP4072




CCTTHP4272



CCTTHP4872




CCTTHP5472




CCTTHP5672


86 1/2"(2197)
88 1/16"(2237)
84 3/4"(2153)
84"(2134)
75 9/16"(1919)




CCTTHP4084




CCTTHP4284



CCTTHP4884



CCTTHP5484



CCTTHP5684

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING


Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

63 1/4"(1607)
66 5/16"(1118)
60 3/4"(1543)
60"(1524)
51 9/16"(1310)

20 1/2"(521)
22 1/16"(5660)
18 3/4"(476)
18"(457)
9 9/16"(243)




CCTTHP6018

22 1/2"(572)
24 1/16"(611)
20 3/4"(527)
20"(508)
11 9/16"(294)




CCTTHP6020

26 1/2"(673)
28 1/16"(713)
24 3/4"(629)
24"(610)
15 9/16"(395)



CCTTHP6024

32 1/2"(826)
34 1/16"(865)
30 3/4"(781)
30"(762)
21 9/16"(547)



CCTTHP6030

34 1/2"(876)
36 1/16"(916)
32 3/4"(832)
32"(813)
23 9/16"(598)




CCTTHP6032

38 1/2"(978)
40 1/16"(1018)
36 3/4"(933)
36"(914)
27 9/16"(700)



CCTTHP6036

42 1/2"(1080)
44 1/16"(1119)
40 3/4"(1035)
40"(1016)
31 9/16"(802)



CCTTHP6040

44 1/2"(1130)
46 1/16"(1170)
42 3/4"(1086)
42"(1067)
33 9/16"(852)




CCTTHP6042

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING


63 1/4"(1607)
66 5/16"(1118)
60 3/4"(1543)
60"(1524)
51 9/16"(1310)

50 1/2"(1283)
52 1/16"(1322)
48 3/4"(1238)
48"(1219)
39 9/16"(1005)




CCTTHP6048

56 1/2"(1435)
58 1/16"(1475)
54 3/4"(1391)
54"(1372)
45 9/16"(1157)




CCTTHP6054

58 1/2"(1486)
60 1/16"(1526)
56 3/4"(1441)
56"(1422)
47 9/16"(1208)




CCTTHP6056

62 1/2"(1588)
64 1/16"(1627)
60 3/4"(1543)
60"(1524)
51 9/16"(1310)



CCTTHP6060

66 1/2"(1689)
68 1/16"(1729)
64 3/4"(1645)
64"(1626)
55 9/16"(1411)



CCTTHP6064

ELEVATION SYMBOL LEGEND:


M.O. = MASORY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS


MO BRICKMOLD 63 1/4"(1607)
MO FLAT CASING 66 5/16"(1118)
ROUGH OPENING 60 3/4"(1543)
FRAME SIZE 60"(1524)
DAYLIGHT OPENING 51 9/16"(1310)

68 1/2"(1740)
70 1/16"(1780)
66 3/4"(1695)
66"(1676)
57 9/16"(1462)




CCTTHP6066

74 1/2"(1892)
76 1/16"(1932)
72 3/4"(1848)
72"(1829)
63 9/16"(1614)



CCTTHP6072

86 1/2"(2197)
88 1/16"(2237)
84 3/4"(2153)
84"(2134)
75 9/16"(1919)



CCTTHP6084

ELEVATION SYMBOL LEGEND:
M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

2 WIDE UNIT ELEVATIONS
















MO BRICKMOLD MO FLAT CASING ROUGH OPENING FRAME SIZE DAYLIGHT OPENING	51 1/4"(1302) 54 5/16"(1380) 48 3/4"(1238) 48"(1219) 15 9/16"(395)[2]	59 1/4"(1505) 62 5/16"(1583) 56 3/4"(1441) 56"(1422) 19 9/16"(497)[2]	63 1/4"(1607) 66 5/16"(1684) 60 3/4"(1543) 60"(1524) 21 9/16"(547)[2]	67 1/4"(1708) 70 5/16"(1786) 64 3/4"(1645) 64"(1626) 23 9/16"(598)[2]	75 1/4"(1911) 78 5/16"(1989) 72 3/4"(1848) 72"(1829) 27 9/16"(700)[2]
20 1/2"(521) 22 1/2"(572) 20 1/2"(521) 24 1/16"(611) 22 1/16"(560) 20 3/4"(527) 18 3/4"(476) 18"(457) 20"(508) 18"(457) 11 9/16"(294) 9 9/16"(243)					
22 1/2"(572) 24 1/16"(611) 20 3/4"(527) 20"(508) 24 1/16"(611) 20 3/4"(527) 20"(508) 15 9/16"(395) 11 9/16"(294) 9 9/16"(243)					
26 1/2"(673) 28 1/16"(713) 24 3/4"(629) 24"(610) 26 1/2"(673) 28 1/16"(713) 24 3/4"(629) 24"(610) 15 9/16"(395) 11 9/16"(294) 9 9/16"(243)					
32 1/2"(826) 34 1/16"(865) 30 3/4"(781) 30"(762) 32 1/2"(826) 34 1/16"(865) 30 3/4"(781) 30"(762) 21 9/16"(547)					
34 1/2"(876) 36 1/16"(916) 32 3/4"(832) 32"(813) 34 1/2"(876) 36 1/16"(916) 32 3/4"(832) 32"(813) 23 9/16"(598)					
38 1/2"(978) 40 1/16"(1018) 36 3/4"(933) 36"(914) 38 1/2"(978) 40 1/16"(1018) 36 3/4"(933) 36"(914) 27 9/16"(700)					
42 1/2"(1080) 44 1/16"(1119) 40 3/4"(1035) 40"(1016) 42 1/2"(1080) 44 1/16"(1119) 40 3/4"(1035) 40"(1016) 31 9/16"(802)					
44 1/2"(1130) 46 1/16"(1170) 42 3/4"(1067) 42"(1048) 44 1/2"(1130) 46 1/16"(1170) 42 3/4"(1067) 42"(1048) 33 9/16"(852)					
50 1/2"(1283) 52 1/16"(1322) 48 3/4"(1238) 48"(1219) 50 1/2"(1283) 52 1/16"(1322) 48 3/4"(1238) 48"(1219) 39 9/16"(1005)					
56 1/2"(1435) 58 1/16"(1475) 54 3/4"(1391) 54"(1372) 56 1/2"(1435) 58 1/16"(1475) 54 3/4"(1391) 54"(1372) 45 9/16"(1157)					
58 1/2"(1486) 60 1/16"(1526) 56 3/4"(1441) 56"(1422) 58 1/2"(1486) 60 1/16"(1526) 56 3/4"(1441) 56"(1422) 47 9/16"(1208)					
62 1/2"(1588) 64 1/16"(1627) 60 3/4"(1543) 60"(1524) 62 1/2"(1588) 64 1/16"(1627) 60 3/4"(1543) 60"(1524) 51 9/16"(1310)					

ELEVATION SYMBOL LEGEND:
M.O. = MASONRY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
VALUES IN [] ARE NUMBER OF DAYLIGHT OPENING PER UNIT
* AVAILABLE ONLY AS A STATIONARY WINDOW

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

2 WIDE UNIT ELEVATIONS

MO BRICKMOLD	51 1/4"(1302)	59 1/4"(1505)	63 1/4"(1607)	67 1/4"(1708)	75 1/4"(1911)
MO FLAT CASING	54 5/16"(1380)	62 5/16"(1583)	66 5/16"(1684)	70 5/16"(1786)	78 5/16"(1989)
ROUGH OPENING	48 3/4"(1238)	56 3/4"(1441)	60 3/4"(1543)	64 3/4"(1645)	72 3/4"(1848)
FRAME SIZE	48"(1219)	56"(1422)	60"(1524)	64"(1626)	72"(1829)
DAYLIGHT OPENING	15 9/16"(395)[2]	19 9/16"(497)[2]	21 9/16"(547)[2]	23 9/16"(598)[2]	27 9/16"(700)[2]

66 1/2"(1689)					
68 1/16"(1729)	CCTTH2464-2	CCTTH2864-2	CCTTH3064-2	CCTTH3264-2	CCTTH3664-2
64 3/4"(1645)					
64"(1626)	CCTTH2466-2	CCTTH2866-2	CCTTH3066-2	CCTTH3266-2	CCTTH3666-2
55 9/16"(1411)					
74 1/2"(1892)	CCTTH2472-2	CCTTH2872-2	CCTTH3072-2	CCTTH3272-2	CCTTH3672-2
76 1/16"(1932)					
72 3/4"(1848)					
72"(1829)					
63 9/16"(1614)					

ELEVATION SYMBOL LEGEND:
M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
VALUES IN [] ARE NUMBER OF DAYLIGHT OPENING PER UNIT
* AVAILABLE ONLY AS A STATIONARY WINDOW

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

3 WIDE UNIT ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

75 1/4"(1911)
78 5/16"(1989)
72 3/4"(1848)
72"(1829)
15 9/16"(395)[3]

87 1/4"(2216)
90 5/16"(2294)
84 3/4"(2153)
84"(2134)
19 9/16"(497)[3]

93 1/4"(2369)
96 5/16"(2446)
90 3/4"(2305)
90"(2286)
21 9/16"(547)[3]

99 1/4"(2521)
102 5/16"(2599)
96 3/4"(2457)
96"(2438)
23 9/16"(598)[3]

111 1/4"(2856)
114 5/16"(2904)
108 3/4"(2762)
108"(2743)
27 9/16"(700)[3]

20 1/2"(521)
22 1/2"(572)
24 1/16"(611)
24 3/4"(629)
26 1/2"(673)
28 1/16"(713)
30 3/4"(781)
307(762)
32 1/2"(826)
34 1/16"(865)
36 1/16"(916)
32 3/4"(832)
32"(813)
38 1/2"(978)
40 1/16"(1018)
36 3/4"(933)
36"(914)
42 1/2"(1080)
44 1/16"(1119)
40 3/4"(1035)
40"(1016)
44 1/2"(1130)
46 1/16"(1170)
42 3/4"(1067)
42"(1067)
50 1/2"(1283)
52 1/16"(1322)
48 3/4"(1238)
48"(1219)
56 1/2"(1435)
58 1/16"(1475)
54 3/4"(1391)
54"(1372)
58 1/2"(1486)
60 1/16"(1526)
56 3/4"(1441)
56"(1422)
64 1/2"(1588)
60 1/16"(1627)
60 3/4"(1543)
60"(1524)
61 9/16"(1572)
61 9/16"(1572)
61 9/16"(1572)



CCTTH2418-3




CCTTH2420-3



CCTTH2424-3



CCTTH2430-3




CCTTH2432-3



CCTTH2436-3



CCTTH2440-3




CCTTH2442-3



CCTTH2448-3



CCTTH2454-3



CCTTH2456-3



CCTTH2460-3



CCTTH2818-3



CCTTH2820-3



CCTTH2824-3



CCTTH2830-3




CCTTH2832-3



CCTTH2836-3



CCTTH2840-3




CCTTH2842-3



CCTTH2848-3



CCTTH2854-3



CCTTH2856-3



CCTTH2860-3



CCTTH3018-3



CCTTH3020-3



CCTTH3024-3



CCTTH3030-3




CCTTH3032-3



CCTTH3036-3



CCTTH3040-3



CCTTH3042-3



CCTTH3048-3



CCTTH3054-3



CCTTH3056-3



CCTTH3060-3



CCTTH3218-3



CCTTH3220-3



CCTTH3224-3



CCTTH3230-3




CCTTH3232-3



CCTTH3236-3



CCTTH3240-3




CCTTH3242-3



CCTTH3248-3



CCTTH3254-3



CCTTH3256-3



CCTTH3260-3



CCTTH3618-3




CCTTH3620-3



CCTTH3624-3



CCTTH3630-3




CCTTH3632-3



CCTTH3636-3



CCTTH3640-3




CCTTH3642-3



CCTTH3648-3



CCTTH3654-3



CCTTH3656-3



CCTTH3660-3

ELEVATION SYMBOL LEGEND:
M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
VALUES IN [] ARE NUMBER OF DAYLIGHT OPENING PER UNIT
* AVAILABLE ONLY AS A STATIONARY WINDOW

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

3 WIDE UNIT ELEVATIONS

MO BRICKMOLD
MO FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

75 1/4"(1911)
78 5/16"(1989)
72 3/4"(1848)
72"(1829)
15 9/16"(395)[3]


87 1/4"(2216)
90 5/16"(2294)
84 3/4"(2153)
84"(2134)
19 9/16"(497)[3]

93 1/4"(2369)
96 5/16"(2446)
90 3/4"(2305)
90"(2286)
21 9/16"(547)[3]


99 1/4"(2521)
102 5/16"(2599)
96 3/4"(2457)
96"(2438)
23 9/16"(598)[3]

111 1/4"(2856)
114 5/16"(2904)
108 3/4"(2762)
108"(2743)
27 9/16"(700)[3]


66 1/2"(1689)
68 1/16"(1729)
64 3/4"(1645)
64"(1626)
55 9/16"(1411)




CCTTH2464-3




CCTTH2864-3



CCTTH3064-3




CCTTH3264-3




CCTTH3664-3


68 1/2"(1740)
70 1/16"(1780)
66 3/4"(1695)
66"(1676)
57 9/16"(1462)




CCTTH2466-3




CCTTH2866-3



CCTTH3066-3




CCTTH3266-3




CCTTH3666-3


74 1/2"(1892)
76 1/16"(1932)
72 3/4"(1848)
72"(1829)
63 9/16"(1614)




CCTTH2472-3




CCTTH2872-3



CCTTH3072-3



CCTTH3272-3



CCTTH3672-3

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
VALUES IN [] ARE NUMBER OF DAYLIGHT OPENING PER UNIT
* AVAILABLE ONLY AS A STATIONARY WINDOW

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.