
TABLE OF CONTENTS

Single Unit	11-2
Picture Unit	11-4
Transom Unit	11-5

ELEVATIONS
SINGLE UNITS

MO BRICKMOLD	35 5/16"(897)	47 5/16"(1202)	59 5/16"(1507)	71 5/16"(1811)
MO FLAT CASING	38 3/8"(975)	50 3/8"(1280)	62 3/8"(1584)	74 3/8"(1889)
ROUGH OPENING	32 15/16"(837)	44 15/16"(1141)	56 15/16"(1446)	68 15/16"(1751)
FRAME SIZE	32 3/16"(818)	44 3/16"(1122)	56 3/16"(1427)	68 3/16"(1732)
DAYLIGHT OPENING	22 5/16"(567)	34 5/16"(872)	46 5/16"(1176)	58 5/16"(1481)

59 1/2"(1511) 61"(1549) 57 13/16"(1468) 57 1/16"(1449) 22 1/4"(565)				
CWED3257	CWED4457	CWED5657	CWED6857	
83 1/2"(2121) 85"(2159) 81 13/16"(2078) 81 1/16"(2059) 34 1/4"(870)				
CWED3281	CWED4481	CWED5681	CWED6881	
107 1/2"(2731) 109"(2769) 105 13/16"(2688) 105 1/16"(2669) 46 1/4"(1175)				
CWED32105	CWED44105	CWED56105	CWED68105	
131 1/2"(3340) 133"(3378) 129 13/16"(3297) 129 1/16"(3278) 58 1/4"(1480)				
CWED32129	CWED44129	CWED56129	CWED68129	

ELEVATION SYMBOL LEGEND:

- VALUES IN () ARE IN MILLIMETER CONVERSIONS.
- E BASIC UNIT CLEAR OPENING EXCEEDS 20" IN WIDTH, 24" IN HEIGHT & A MINIMUM OF 5.7 SQ. FT.
- F SASH TRAVEL RESTRICTED, UPPER SASH FIXED.
- ##* NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING.
- ALL OPERABLE UNITS ARE AVAILABLE IN A SINGLE-HUNG CONFIGURATION WITH A FIXED UPPER SASH.

Note: Elevations shown include brickmold. Subtract 1/2"(12.7) from M.O. (Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

ELEVATIONS
SINGLE UNITS

MO BRICKMOLD	35 7/16"(900)	47 7/16"(1205)	59 7/16"(1510)	71 7/16"(1815)
MO FLAT CASING	38 1/2"(998)	50 1/2"(1283)	62 1/2"(1588)	74 1/2"(1892)
ROUGH OPENING	32 15/16"(837)	44 15/16"(1141)	56 15/16"(1446)	68 15/16"(1751)
FRAME SIZE	32 3/16"(818)	44 3/16"(1122)	56 3/16"(1427)	68 3/16"(1732)
DAYLIGHT OPENING	22 5/16"(567)	34 5/16"(872)	46 5/16"(1176)	58 5/16"(1481)

<p>83 1/2"(2121) 85"(2159) 81 13/16"(2078) 81 1/16"(2059) (UPR) 25 5/8"(651) (LWR) 42 13/16"(1087)</p>				
	CWED3281C47	CWED4481C47	CWED5681C47	CWED6881C47
<p>107 1/2"(2731) 109"(2769) 105 13/16"(2688) 105 1/16"(2669) (UPR) 37"(940) (LWR) 55 1/2"(1410)</p>				
	CWED32105C59	CWED44105C59	CWED56105C59	CWED68105C59
<p>83 1/2"(2121) 85"(2159) 81 13/16"(2078) 81 1/16"(2059) (UPR) 42 13/16"(1087) (LWR) 25 5/8"(651)</p>				
	CWED3281R23	CWED4481R23	CWED5681R23	CWED6881R23
<p>107 1/2"(2731) 109"(2769) 105 13/16"(2688) 105 1/16"(2669) (UPR) 55 1/2"(1410) (LWR) 37"(940)</p>				
	CWED32105R35	CWED44105R35	CWED56105R35	CWED68105R35

ELEVATION SYMBOL LEGEND:

- VALUES IN () ARE IN MILLIMETER CONVERSIONS.
- E BASIC UNIT CLEAR OPENING EXCEEDS 20" IN WIDTH, 24" IN HEIGHT & A MINIMUM OF 5.7 SQ. FT.
- F SASH TRAVEL RESTRICTED, UPPER SASH FIXED.
- ## NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING.
- ALL OPERABLE UNITS ARE AVAILABLE IN A SINGLE-HUNG CONFIGURATION WITH A FIXED UPPER SASH.

Note: Elevations shown include brickmold. Subtract 1/2" (12.7) from M.O. (Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

ELEVATIONS
PICTURE UNITS

MO BRICKMOLD	35 7/16"(900)	47 7/16"(1205)	59 7/16"(1510)	71 7/16"(1815)
MO FLAT CASING	38 1/2"(998)	50 1/2"(1283)	62 1/2"(1588)	74 1/2"(1892)
ROUGH OPENING	32 15/16"(837)	44 15/16"(1141)	56 15/16"(1446)	68 15/16"(1751)
FRAME SIZE	32 3/16"(818)	44 3/16"(1122)	56 3/16"(1427)	68 3/16"(1732)
DAYLIGHT OPENING	22 5/16"(567)	34 5/16"(872)	46 5/16"(1176)	58 5/16"(1481)

59 1/2"(1511) 61 1/32"(1550) 57 13/16"(1468) 57 1/16"(1449) 46 23/32"(1187)				
CWEDP3257	CWEDP4457	CWEDP5657	CWEDP6857	
83 1/2"(2121) 85 1/32"(2160) 81 13/16"(2078) 81 1/16"(2059) 70 23/32"(1796)				
CWEDP3281	CWEDP4481	CWEDP5681	CWEDP6881	
107 1/2"(2731) 109 1/32"(2769) 105 13/16"(2688) 105 1/16"(2669) 94 23/32"(2406)				
CWEDP32105	CWEDP44105	CWEDP56105	CWEDP68105	
131 1/2"(3340) 133 1/32"(3379) 129 13/16"(3278) 129 1/16"(3278) 118 23/32"(3015)				
CWEDP32129	CWEDP44129	CWEDP56129	CWEDP68129	

ELEVATION SYMBOL LEGEND:

VALUES IN () ARE IN MILLIMETER CONVERSIONS.

##* NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING.

Note: Elevations shown include brickmould. Subtract 1/2"(12.7) from M.O. (Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

ELEVATIONS
TRANSOM UNITS

	35 7/16"(900)	47 7/16"(1205)	59 7/16"(1510)	71 7/16"(1815)
MO BRICKMOLD	35 7/16"(900)	47 7/16"(1205)	59 7/16"(1510)	71 7/16"(1815)
MO FLAT CASING	38 1/2"(998)	50 1/2"(1283)	62 1/2"(1588)	74 1/2"(1892)
ROUGH OPENING	32 15/16"(837)	44 15/16"(1141)	56 15/16"(1446)	68 15/16"(1751)
FRAME SIZE	32 3/16"(818)	44 3/16"(1122)	56 3/16"(1427)	68 3/16"(1732)
DAYLIGHT OPENING	22 5/16"(567)	34 5/16"(872)	46 5/16"(1176)	58 5/16"(1481)
35 1/16"(891)				
36 9/16"(925)	CWEDT3232	CWEDT4432	CWEDT5632	CWEDT6832
33 3/8"(848)				
32 5/8"(829)	CWEDT3244	CWEDT4444	CWEDT5644	CWEDT6844
22 9/32"(567)				
47 1/16"(890)	CWEDT3256	CWEDT4456	CWEDT5656	CWEDT6856
48 9/16"(1233)				
45 3/8"(1152)	CWEDT3268	CWEDT4468	CWEDT5668	CWEDT6868
44 5/8"(1133)				
34 9/32"(871)	CWEDT3268	CWEDT4468	CWEDT5668	CWEDT6868
59 1/16"(1500)				
60 9/16"(1538)	CWEDT3268	CWEDT4468	CWEDT5668	CWEDT6868
57 3/8"(1457)				
56 5/8"(1432)	CWEDT3268	CWEDT4468	CWEDT5668	CWEDT6868
46 9/32"(1176)				
71 1/16"(1805)	CWEDT3268	CWEDT4468	CWEDT5668	CWEDT6868
72 9/16"(1843)				
69 3/8"(1762)	CWEDT3268	CWEDT4468	CWEDT5668	CWEDT6868
68 5/8"(1743)				
58 9/32"(1480)	CWEDT3268	CWEDT4468	CWEDT5668	CWEDT6868

ELEVATION SYMBOL LEGEND:

VALUES IN () ARE IN MILLIMETER CONVERSIONS.

NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING.

Note: Elevations shown include standard brickmould and sill nosing. Subtract 1/2"(12.7) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.