

---

ELEVATIONS TABLE OF CONTENTS

---

Swinging Door Units . . . . .	23-30
French Units . . . . .	23-36
Single Door with Single Sidelite . . . . .	23-40
Single Door with Two Sidelites . . . . .	23-41
French Door with Two Sidelites . . . . .	23-42
Transom Units . . . . .	23-46
Sector Top Doors . . . . .	23-51
French Sector Top Doors . . . . .	23-55
French Sector Top Doors with Two Sidelites . . . . .	23-56
Sector Top Transom Units . . . . .	23-60
Venting Sidelight Units . . . . .	23-61

**ELEVATIONS**  
**1- PANEL UNITS**

	16 11/16" [424]	18 11/16" [475]	20 11/16" [525]	28 9/16" [725]	34 9/16" [878]	36 9/16" [929]	40 9/16" [1030]	46 9/16" [1183]
M.O. Brickmould	19 7/8" [505]	21 3/4" [552]	23 3/4" [603]	31 5/8" [803]	37 5/8" [956]	39 5/8" [1006]	43 5/8" [1108]	49 5/8" [1260]
M.O. Adams/Flat Casing	14 1/16" [357]	16 1/16" [408]	18 1/16" [459]	26 3/16" [665]	32 3/16" [818]	34 3/16" [868]	38 3/16" [970]	44 3/16" [1122]
Rough Opening	13 9/16" [344]	15 9/16" [395]	17 9/16" [446]	25 7/16" [646]	31 7/16" [799]	33 7/16" [849]	37 7/16" [951]	43 7/16" [1103]
Frame Size	7 1/2" [190]	8 1/2" [216]	11 1/2" [292]	14 5/8" [371]	20 5/8" [524]	22 5/8" [575]	26 5/8" [676]	32 5/8" [829]
Daylight Opening								
84 5/16" [2142]								
85 27/32" [2180]								
83 1/4" [2115]								
82 1/2" [2096]								
68 11/16" [1745]								
88 5/16" [2243]								
89 27/32" [2282]								
87 1/4" [2216]								
86 1/2" [2197]								
72 11/16" [1846]								
100 5/16" [2548]								
101 27/32" [2587]								
99 1/4" [2521]								
98 1/2" [2502]								
84 11/16" [2151]								
112 5/16" [2853]								
113 27/32" [2892]								
111 1/4" [2826]								
110 1/2" [2807]								
96 11/16" [2456]								

**ELEVATION SYMBOL LEGEND:**

PANEL IS AVAILABLE AS FIXED ONLY

**##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**1- PANEL UNITS**

M.O. Brickmould	26 9/16" [675]	32 9/16" [827]	34 9/16" [878]	38 9/16" [979]
M.O. Adams/Flat Casing	29 5/8" [752]	35 5/8" [905]	37 5/8" [956]	41 5/8" [1057]
Rough Opening	24 3/16" [614]	30 3/16" [767]	32 3/16" [818]	36 3/16" [919]
Frame Size	23 7/16" [595]	29 7/16" [748]	31 7/16" [799]	35 7/16" [900]
Daylight Opening	12 5/8" [321]	18 5/8" [473]	20 5/8" [524]	24 5/8" [625]

81 5/16" [2065]  
82 27/32" [2104]  
80 1/4" [2038]  
79 1/2" [2019]  
65 11/16" [1668]



WISWR2068



WISWR2668



WISWR2868



WISWR3068

97 5/16" [2472]  
98 27/32" [2511]  
96 1/4" [2445]  
95 1/2" [2426]  
81 11/16" [2075]



WISWR2080



WISWR2680



WISWR2880




WISWR3080


109 5/16" [2777]  
110 27/32" [2815]  
108 1/4" [2750]  
107 1/2" [2731]  
93 11/16" [2380]




WISWR2090



WISWR2690



WISWR2890



WISWR3090

**ELEVATION SYMBOL LEGEND:**

- (F) PANEL IS AVAILABLE AS FIXED ONLY
- ## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.
- M.O. = MASONRY OPENING
- VALUES IN [ ] ARE MILLIMETER CONVERSIONS
- VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**2- PANEL UNITS**

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening


65 3/4" [1670]  
68 13/16" [1748]  
63 3/8" [1610]  
62 5/8" [1591]  
20 5/8" [524] (2)

69 3/4" [1772]  
72 13/16" [1849]  
67 3/8" [1711]  
66 5/8" [1692]  
22 5/8" [575] (2)


77 3/4" [1975]  
80 13/16" [2053]  
75 3/8" [1915]  
74 5/8" [1895]  
26 5/8" [676] (2)

89 3/4" [2280]  
92 13/16" [2357]  
87 3/8" [2219]  
86 5/8" [2200]  
32 5/8" [829] (2)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2096]  
68 11/16" [1745]




WISWT5068



WISWT5468




WISWT6068




WISWT7068


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2215]  
86 1/2" [2197]  
72 11/16" [1846]




WISWT5070



WISWT5470




WISWT6070




WISWT7070


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]




WISWT5080



WISWT5480




WISWT6080




WISWT7080


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WISWT5090



WISWT5490



WISWT6090

**ELEVATION SYMBOL LEGEND:**

Ⓡ PANEL IS AVAILABLE AS FIXED ONLY

## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS  
2- PANEL UNITS**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

61 3/4" [1568]  
64 13/16" [1646]  
59 3/8" [1508]  
58 5/8" [1489]  
18 5/8" [473] (2)


65 3/4" [1670]  
68 13/16" [1748]  
63 3/8" [1610]  
62 5/8" [1591]  
20 5/8" [524] (2)

73 3/4" [1873]  
76 13/16" [1951]  
71 3/8" [1813]  
70 5/8" [1794]  
24 5/8" [625] (2)


81 5/16" [2065]  
82 27/32" [2104]  
80 1/4" [2038]  
79 1/2" [2019]  
65 11/16" [1668]



WISWR5068




WISWR5468




WISWR6068


97 5/16" [2472]  
98 27/32" [2511]  
96 1/4" [2445]  
95 1/2" [2426]  
81 11/16" [2075]



WISWR5080




WISWR5480




WISWR6080


109 5/16" [2777]  
110 27/32" [2815]  
108 1/4" [2750]  
107 1/2" [2731]  
93 11/16" [2380]



WISWR5090



WISWR5490



WISWR6090

**ELEVATION SYMBOL LEGEND:**

- (F)** PANEL IS AVAILABLE AS FIXED ONLY
- ##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**CUSTOM WOOD PATIO DOORS**  
CUSTOM IN-SWING

**ELEVATIONS**  
**3-PANEL UNITS**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

96 15/16" [2462]  
100" [2540]  
94 9/16" [2402]  
93 13/16" [2383]  
20 5/8" [524] (3)


102 15/16" [2615]  
106" [2692]  
100 9/16" [2554]  
99 13/16" [2535]  
22 5/8" [575] (3)

114 15/16" [2919]  
118" [2997]  
112 9/16" [2859]  
111 13/16" [2840]  
26 5/8" [676] (3)


84 5/16" [2142]  
85 27/32" [2160]  
83 1/4" [2036]  
82 1/2" [2096]  
88 11/16" [1745]



WISWT7668




WISWT8068




WISWT9068


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WISWT7670




WISWT8070




WISWT9070


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WISWT7680




WISWT8080




WISWT9080


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WISWT7690



WISWT8090



WISWT9090

- ELEVATION SYMBOL LEGEND:**
- (F)** PANEL IS AVAILABLE AS FIXED ONLY
  - ##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.
  - M.O.** = MASONRY OPENING
  - VALUES IN [ ] ARE MILLIMETER CONVERSIONS
  - VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**3-PANEL UNITS**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

90 15/16" [2310]  
94" [2388]  
88 9/16" [2250]  
87 13/16" [2230]  
18 5/8" [473] (3)


96 15/16" [2462]  
100" [2540]  
94 9/16" [2402]  
93 13/16" [2383]  
20 5/8" [524] (3)

108 15/16" [2767]  
112" [2845]  
106 9/16" [2707]  
105 13/16" [2688]  
24 5/8" [625] (3)


81 5/16" [2065]  
82 27/32" [2104]  
80 1/4" [2038]  
79 1/2" [2019]  
65 11/16" [1695]



WISWR7668




WISWR8068




WISWR9068


97 5/16" [2472]  
98 27/32" [2511]  
96 1/4" [2445]  
95 1/2" [2426]  
81 11/16" [2075]



WISWR7680




WISWR8080




WISWR9080


109 5/16" [2777]  
110 27/32" [2815]  
108 1/4" [2750]  
107 1/2" [2731]  
93 11/16" [2380]



WISWR7690



WISWR8090



WISWR9090

**ELEVATION SYMBOL LEGEND:**

Ⓡ PANEL IS AVAILABLE AS FIXED ONLY

## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING

VALUES IN [ ] ARE MILLIMETER CONVERSIONS

VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS  
FRENCH DOOR UNITS**

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

53 3/4" [1365]  
56 13/16" [1443]  
51 3/8" [1305]  
50 5/8" [1286]  
14 5/8" [371] (2)


65 3/4" [1670]  
68 13/16" [1748]  
63 3/8" [1610]  
62 5/8" [1591]  
20 5/8" [524] (2)

69 3/4" [1772]  
72 13/16" [1849]  
67 3/8" [1711]  
66 5/8" [1692]  
22 5/8" [575] (2)


77 3/4" [1975]  
80 13/16" [2053]  
75 3/8" [1915]  
74 5/8" [1895]  
26 5/8" [676] (2)

89 3/4" [2280]  
92 13/16" [2357]  
87 3/8" [2219]  
86 5/8" [2200]  
32 5/8" [829] (2)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2096]  
68 11/16" [1746]




WIFRT4068




WIFRT5068



WIFRT5468




WIFRT6068




WIFRT7068


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]




WIFRT4070




WIFRT5070



WIFRT5470




WIFRT6070




WIFRT7070


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]




WIFRT4080




WIFRT5080



WIFRT5480




WIFRT6080




WIFRT7080


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]




WIFRT4090



WIFRT5090



WIFRT5490



WIFRT6090

**ELEVATION SYMBOL LEGEND:**

- (F) PANEL IS AVAILABLE AS FIXED ONLY
- ## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.



**ELEVATIONS**  
**FRENCH DOOR UNITS**

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening


49 3/4" [1264]  
52 13/16" [1341]  
47 3/8" [1203]  
46 5/8" [1184]  
12 5/8" [321] (2)

61 3/4" [1568]  
64 13/16" [1646]  
59 3/8" [1508]  
58 5/8" [1489]  
18 5/8" [473] (2)


65 3/4" [1670]  
68 13/16" [1748]  
63 3/8" [1610]  
62 5/8" [1591]  
20 5/8" [524] (2)

73 3/4" [1873]  
76 13/16" [1951]  
71 3/8" [1813]  
70 5/8" [1794]  
24 5/8" [625] (2)


81 5/16" [2065]  
82 27/32" [2104]  
80 1/4" [2038]  
79 1/2" [2019]  
65 11/16" [1668]




WIFRR4068



WIFRR5068




WIFRR5468




WIFRR6068


97 5/16" [2472]  
98 27/32" [2511]  
96 1/4" [2445]  
95 1/2" [2426]  
81 11/16" [2075]




WIFRR4080



WIFRR5080




WIFRR5480




WIFRR6080


109 5/16" [2777]  
110 27/32" [2815]  
108 1/4" [2750]  
107 1/2" [2731]  
93 11/16" [2380]




WIFRR4090



WIFRR5090



WIFRR5490



WIFRR6090

**ELEVATION SYMBOL LEGEND:**

**F** PANEL IS AVAILABLE AS FIXED ONLY

**##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**4-PANEL FRENCH DOOR UNITS**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

104 1/8" [2645]  
107 3/16" [2723]  
101 3/4" [2584]  
101" [2565]  
14 5/8" [371] (4)


128 1/8" [3254]  
131 3/16" [3332]  
125 3/4" [3194]  
125" [3175]  
20 5/8" [524] (4)

152 1/8" [3864]  
155 3/16" [3942]  
149 3/4" [3804]  
149" [3785]  
26 5/8" [676] (4)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2038]  
82 1/2" [2096]  
68 11/16" [1745]



WIFRT8068




WIFRT10068




WIFRT12068


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRT8070




WIFRT10070




WIFRT12070


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRT8080




WIFRT10080




WIFRT12080


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRT8090



WIFRT10090



WIFRT12090

**ELEVATION SYMBOL LEGEND:**

**F** PANEL IS AVAILABLE AS FIXED ONLY

**#** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**4-PANEL FRENCH DOOR UNITS**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

96 1/8" [2442]  
99 3/16" [2519]  
93 3/4" [2381]  
93" [2362]  
12 5/8" [321] (4)


120 1/8" [3051]  
123 3/16" [3129]  
117 3/4" [2991]  
117" [2972]  
18 5/8" [473] (4)

144 1/8" [3661]  
147 3/16" [3739]  
141 3/4" [3600]  
141" [3581]  
24 5/8" [625] (4)


81 5/16" [2065]  
82 27/32" [2104]  
80 1/4" [2038]  
79 1/2" [2019]  
65 11/16" [1695]



WIFRR8068




WIFRR10068




WIFRR12068


97 5/16" [2472]  
98 27/32" [2511]  
96 1/4" [2445]  
95 1/2" [2426]  
81 11/16" [2075]



WIFRR8080




WIFRR10080




WIFRR12080


109 5/16" [2777]  
110 27/32" [2815]  
108 1/4" [2750]  
107 1/2" [2731]  
93 11/16" [2380]



WIFRR8090



WIFRR10090



WIFRR12090

**ELEVATION SYMBOL LEGEND:**

(F) PANEL IS AVAILABLE AS FIXED ONLY

## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**1-PANEL W/ SIDELITE UNITS**

M.O. Brickmould	53 7/8" [1368]	55 7/8" [1419]	57 7/8" [1470]	59 7/8" [1521]	61 7/8" [1572]	63 7/8" [1622]
M.O. Adams/Flat Casing	56 15/16" [1446]	58 15/16" [1497]	60 15/16" [1548]	62 15/16" [1599]	64 15/16" [1649]	66 15/16" [1700]
Rough Opening	51 1/2" [1308]	53 1/2" [1359]	55 1/2" [1410]	57 1/2" [1460]	59 1/2" [1511]	61 1/2" [1562]
Frame Size	50 3/4" [1289]	52 3/4" [1340]	54 3/4" [1391]	56 3/4" [1441]	58 3/4" [1492]	60 3/4" [1543]
Daylight Opening	7 1/2" [190]	9 1/2" [241]	11 1/2" [292]	7 1/2" [190]	9 1/2" [241]	11 1/2" [292]
	26 5/8" [676]	26 5/8" [676]	26 5/8" [676]	32 5/8" [829]	32 5/8" [829]	32 5/8" [829]
84 5/16" [2142]						
85 27/32" [2180]	WISWT3068B10	WISWT3068B12	WISWT3068B14	WISWT3668B10	WISWT3668B12	WISWT3668B14
83 1/4" [2114]						
82 1/2" [2096]	WISWT3070B10	WISWT3070B12	WISWT3070B14	WISWT3670B10	WISWT3670B12	WISWT3670B14
68 11/16" [1745]						
88 5/16" [2243]	WISWT3080B10	WISWT3080B12	WISWT3080B14	WISWT3680B10	WISWT3680B12	WISWT3680B14
89 27/32" [2282]						
87 1/4" [2216]	WISWT3090B10	WISWT3090B12	WISWT3090B14			
86 1/2" [2197]						
72 11/16" [1846]						
100 5/16" [2548]						
101 27/32" [2587]						
99 1/4" [2522]						
98 1/2" [2502]						
84 11/16" [2151]						
112 5/16" [2853]						
113 27/32" [2892]						
111 1/4" [2826]						
110 1/2" [2807]						
96 11/16" [2456]						

**ELEVATION SYMBOL LEGEND:**

**F** PANEL IS AVAILABLE AS FIXED ONLY

**##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**1-PANEL W/ 2 SIDELITES**

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

67 3/16" [1707]  
70 1/4" [1784]  
64 13/16" [1647]  
64 1/16" [1627]  
7 1/2" [190] (2)  
26 5/8" [676]

71 3/16" [1808]  
74 1/4" [1886]  
68 13/16" [1747]  
68 1/16" [1729]  
9 1/2" [241] (2)  
26 5/8" [676]


75 3/16" [1910]  
78 1/4" [1988]  
72 13/16" [1849]  
72 1/16" [1830]  
11 1/2" [292] (2)  
26 5/8" [676]

73 3/16" [1859]  
76 1/4" [1937]  
70 13/16" [1798]  
70 1/16" [1780]  
7 1/2" [190] (2)  
32 5/8" [829]


77 3/16" [1961]  
80 1/4" [2038]  
74 13/16" [1900]  
74 1/16" [1881]  
9 1/2" [241] (2)  
32 5/8" [829]

81 3/16" [2062]  
84 1/4" [2140]  
78 13/16" [2001]  
78 1/16" [1983]  
11 1/2" [292] (2)  
32 5/8" [829]


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2114]  
82 1/2" [2096]  
68 11/16" [1746]




WISWT3068F10




WISWT3068F12




WISWT3068F14



WISWT3668F10




WISWT3668F12




WISWT3668F14


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]




WISWT3070F10




WISWT3070F12




WISWT3070F14



WISWT3670F10




WISWT3670F12




WISWT3670F14


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2522]  
98 1/2" [2502]  
84 11/16" [2151]




WISWT3080F10




WISWT3080F12




WISWT3080F14



WISWT3680F10




WISWT3680F12




WISWT3680F14


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WISWT3090F10



WISWT3090F12



WISWT3090F14

**ELEVATION SYMBOL LEGEND:**  
ⓕ PANEL IS AVAILABLE AS FIXED ONLY

## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**5'-0" WIDE FRENCH DOOR W/ 2 SIDELITES**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

92 3/8" [2346]  
95 7/16" [2424]  
90" [2286]  
89 1/4" [2267]  
7-1/2" [190] (2)  
20 5/8" [524] (2)


96 3/8" [2448]  
99 7/16" [2526]  
94" [2387]  
93 1/4" [2369]  
9 1/2" [241] (2)  
20 5/8" [524] (2)

100 3/8" [2550]  
103 7/16" [2627]  
98" [2489]  
97 1/4" [2470]  
11 1/2" [292] (2)  
20 5/8" [524] (2)


84 5/16" [2142]  
86 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2096]  
68 11/16" [1746]



WIFRT5068Q10




WIFRT5068Q12




WIFRT5068Q14


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRT5070Q10




WIFRT5070Q12




WIFRT5070Q14


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRT5080Q10




WIFRT5080Q12




WIFRT5080Q14


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRT5090Q10



WIFRT5090Q12



WIFRT5090Q14

- ELEVATION SYMBOL LEGEND:**
- (F) PANEL IS AVAILABLE AS FIXED ONLY
  - ## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.
  - M.O. = MASONRY OPENING
  - VALUES IN [ ] ARE MILLIMETER CONVERSIONS
  - VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**5'-4" FRENCH DOOR W/ 2 SIDELITES**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

96 3/8" [2448]  
99 7/16" [2526]  
94" [2387]  
93 1/4" [2369]  
7 1/2" [190] (2)  
22 5/8" [575] (2)


100 3/8" [2550]  
103 7/16" [2627]  
98" [2489]  
97 1/4" [2470]  
9 1/2" [241] (2)  
22 5/8" [575] (2)

104 3/8" [2651]  
107 7/16" [2769]  
102" [2592]  
101 1/4" [2572]  
11 1/2" [292] (2)  
22 5/8" [575] (2)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2114]  
82 1/2" [2096]  
68 11/16" [1745]



WIFRT5468Q10




WIFRT5468Q12




WIFRT5468Q14


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRT5470Q10




WIFRT5470Q12




WIFRT5470Q14


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRT5480Q10




WIFRT5480Q12




WIFRT5480Q14


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRT5490Q10



WIFRT5490Q12



WIFRT5490Q14

**ELEVATION SYMBOL LEGEND:**  
ⓕ PANEL IS AVAILABLE AS FIXED ONLY

## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**6'-0" WIDE FRENCH DOOR W/2 SIDELITES**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

104 3/8" [2651]  
107 7/16" [2729]  
102" [2591]  
101 1/4" [2572]  
7 1/2" [190] (2)  
26 5/8" [575] (2)


108 3/8" [2753]  
111 7/16" [2831]  
106" [2692]  
105 1/4" [2673]  
9 1/2" [241] (2)  
26 5/8" [575] (2)

112 3/8" [2854]  
115 7/16" [2932]  
110" [2794]  
109 1/4" [2775]  
11 1/2" [292] (2)  
26 5/8" [575] (2)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2114]  
82 1/2" [2096]  
68 11/16" [1745]



WIFRT6068Q10




WIFRT6068Q12




WIFRT6068Q14


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRT6070Q10




WIFRT6070Q12




WIFRT6070Q14


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRT6080Q10




WIFRT6080Q12




WIFRT6080Q14


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRT6090Q10



WIFRT6090Q12



WIFRT6090Q14

**ELEVATION SYMBOL LEGEND:**  
Ⓡ PANEL IS AVAILABLE AS FIXED ONLY

## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.



**ELEVATIONS**  
**7'-0" FRENCH DOOR W/2 SIDELITES**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

116 3/8" [2956]  
119 7/16" [3034]  
114" [2894]  
113 1/4" [2877]  
7 1/2" [190] (2)  
32 5/8" [829] (2)


120 3/8" [3058]  
123 7/16" [3135]  
118" [2997]  
117 1/4" [2978]  
9 1/2" [241] (2)  
32 5/8" [829] (2)

124 3/8" [3159]  
127 7/16" [3237]  
122" [3098]  
121 1/4" [3080]  
11 1/2" [292] (2)  
32 5/8" [829] (2)


84 3/8" [2143]  
85 7/8" [2181]  
83 1/4" [2114]  
82 1/2" [2096]  
68 11/16" [1745]



WIFRT7068Q10




WIFRT7068Q12




WIFRT7068Q14


88 3/8" [2245]  
89 7/8" [2283]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRT7070Q10




WIFRT7070Q12




WIFRT7070Q14


100 3/8" [2550]  
101 7/8" [2588]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRT7080Q10



WIFRT7080Q12



WIFRT7080Q14

**ELEVATION SYMBOL LEGEND:**



PANEL IS AVAILABLE AS FIXED ONLY



NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING

VALUES IN [ ] ARE MILLIMETER CONVERSIONS

VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**1- SASH TRANSOM UNITS**

M.O. Brickmould M.O. Adams/Flat Casing <b>Rough Opening</b> Frame Size Daylight Opening	26 9/16" [675] 29 5/8" [752] <b>24 3/16" [614]</b> 23 7/16" [595] 12 5/8" [321]	32 9/16" [827] 35 5/8" [905] <b>30 3/16" [767]</b> 29 7/16" [748] 18 5/8" [473]	34 9/16" [878] 37 5/8" [956] <b>31 15/16" [811]</b> 31 7/16" [799] 21 11/16" [551]	38 9/16" [979] 41 5/8" [1057] <b>36 3/16" [919]</b> 35 7/16" [900] 24 5/8" [625]	49 3/4" [1264] 52 13/16" [1341] <b>47 3/8" [1203]</b> 46 5/8" [1184] 36 13/16" [894]
-----------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------

20 1/2" [521] 22" [559] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]					
32 1/2" [826] 34" [864] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]					

M.O. Brickmould M.O. Adams/Flat Casing <b>Rough Opening</b> Frame Size Daylight Opening	61 3/4" [1568] 64 13/16" [1646] <b>59 3/8" [1507]</b> 58 5/8" [1489] 47 13/16" [1198]	65 3/4" [1670] 68 13/16" [1748] <b>63 1/8" [1603]</b> 62 5/8" [1591] 52 7/8" [1343]	73 3/4" [1873] 76 13/16" [1951] <b>71 3/8" [1813]</b> 70 5/8" [1794] 59 13/16" [1503]
-----------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------

20 1/2" [521] 22" [559] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]			
32 1/2" [826] 34" [864] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]			

M.O. Brickmould M.O. Adams/Flat Casing <b>Rough Opening</b> Frame Size Daylight Opening	16 11/16" [424] 19 3/4" [502] <b>14 5/16" [364]</b> 13 9/16" [344] 7 1/2" [190]	18 11/16" [475] 21 3/4" [552] <b>16 5/16" [414]</b> 15 9/16" [395] 9 1/2" [241]	20 11/16" [525] 23 3/4" [603] <b>18 5/16" [465]</b> 17 9/16" [446] 11 1/2" [292]	28 9/16" [725] 31 5/8" [803] <b>26 3/16" [665]</b> 25 7/16" [646] 14 5/8" [371]	34 9/16" [878] 37 5/8" [956] <b>32 3/16" [817]</b> 31 7/16" [799] 20 5/8" [524]
-----------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------

20 1/2" [521] 22" [559] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]					
32 1/2" [826] 34" [864] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]					

M.O. Brickmould M.O. Adams/Flat Casing <b>Rough Opening</b> Frame Size Daylight Opening	36 9/16" [929] 39 5/8" [1006] <b>34 3/16" [868]</b> 33 7/16" [849] 25 5/8" [575]	40 9/16" [1030] 43 5/8" [1108] <b>38 3/16" [969]</b> 37 7/16" [951] 26 5/8" [676]	46 9/16" [1183] 49 5/8" [1260] <b>44 3/16" [1122]</b> 43 7/16" [1103] 32 5/8" [829]
-----------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------

20 1/2" [521] 22" [559] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]			
32 1/2" [826] 34" [864] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]			

M.O. Brickmould M.O. Adams/Flat Casing <b>Rough Opening</b> Frame Size Daylight Opening	53 3/4" [1365] 56 13/16" [1443] <b>51 3/8" [1304]</b> 62 5/8" [1591] 39 13/16" [1011]	65 3/4" [1670] 68 13/16" [1748] <b>63 3/8" [1610]</b> 62 5/8" [1591] 51 13/16" [1216]	69 3/4" [1772] 72 13/16" [1849] <b>67 3/8" [1711]</b> 66 5/8" [1692] 55 13/16" [1418]	77 3/4" [1975] 80 13/16" [2053] <b>75 3/8" [1914]</b> 74 5/8" [1895] 63 13/16" [1621]	89 3/4" [2280] 92 13/16" [2357] <b>87 3/8" [2219]</b> 86 5/8" [2200] 75 13/16" [1926]
-----------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------

20 1/2" [521] 22" [559] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]					
32 1/2" [826] 34" [864] <b>30 3/4" [781]</b> 30" [762] 22 15/16" [583]					

**ELEVATION SYMBOL LEGEND:**  
 PANEL IS AVAILABLE AS FIXED ONLY  
 ## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
 VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
 VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**2-SASH TRANSOM UNITS**

M.O. Brickmould	49 3/4" [1264]	61 3/4" [1568]	73 3/4" [1873]	53 3/4" [1365]	65 3/4" [1670]
M.O. Adams/Flat Casing	52 13/16" [1341]	64 13/16" [1646]	76 13/16" [1951]	56 13/16" [1443]	68 13/16" [1748]
Rough Opening	47 3/8" [1203]	59 3/8" [1507]	71 3/8" [1813]	51 3/8" [1304]	63 3/8" [1610]
Frame Size	46 5/8" [1184]	58 5/8" [1489]	70 5/8" [1794]	50 5/8" [1286]	62 5/8" [1591]
Daylight Opening	12 5/8" [321] (2)	18 5/8" [473] (2)	24 5/8" [625] (2)	14 5/8" [371] (2)	20 5/8" [524] (2)

20 1/2" [521]  
22" [559]  
18 3/4" [476]  
18" [457]  
10 15/16" [278]



WTISWR4016



WTISWR5016



WTISWR6016



WTISWT4016




WTISWT5016


32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]




WTISWR4026




WTISWR5026



WTISWR6026



WTISWT4026



WTISWT5026

M.O. Brickmould	69 3/4" [1772]	77 3/4" [1975]	89 3/4" [2280]
M.O. Adams/Flat Casing	72 13/16" [1849]	80 13/16" [2053]	92 13/16" [2357]
Rough Opening	67 3/8" [1711]	75 3/8" [1914]	87 3/8" [2219]
Frame Size	66 5/8" [1692]	74 5/8" [1895]	86 5/8" [2200]
Daylight Opening	22 5/8" [575] (2)	26 5/8" [676] (2)	32 5/8" [829] (2)

20 1/2" [521]  
22" [559]  
18 3/4" [476]  
18" [457]  
10 15/16" [278]



WTISWT5416




WTISWT6016




WTISWT7016


32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTISWT5426




WTISWT6026



WTISWT7026

M.O. Brickmould	53 7/8" [1368]	55 7/8" [1419]	57 7/8" [1470]
M.O. Adams/Flat Casing	56 15/16" [1446]	58 15/16" [1497]	60 15/16" [1548]
Rough Opening	51 1/2" [1308]	53 1/2" [1359]	55 1/2" [1410]
Frame Size	50 3/4" [1289]	52 3/4" [1340]	54 3/4" [1391]
Daylight Opening	7 1/2" [190]	9 1/2" [241]	11 1/2" [292]
	26 5/8" [676]	26 5/8" [676]	26 5/8" [676]

20 1/2" [521]  
22" [559]  
18 3/4" [476]  
18" [457]  
10 15/16" [278]



WTISWT3016B10




WTISWT3016B12




WTISWT3016B14


32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTISWT3026B10



WTISWT3026B12




WTISWT3026B14

M.O. Brickmould	59 7/8" [1521]	61 7/8" [1572]	63 7/8" [1622]
M.O. Adams/Flat Casing	62 15/16" [1599]	64 15/16" [1649]	66 15/16" [1700]
Rough Opening	57 1/2" [1460]	59 1/2" [1511]	61 1/2" [1562]
Frame Size	56 3/4" [1441]	58 3/4" [1492]	60 3/4" [1543]
Daylight Opening	7 1/2" [190]	9 1/2" [241]	11 1/2" [292]
	32 5/8" [829]	32 5/8" [829]	32 5/8" [829]

20 1/2" [521]  
22" [559]  
18 3/4" [476]  
18" [457]  
10 15/16" [278]



WTISWT3616B10




WTISWT3616B12




WTISWT3616B14


32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTISWT3626B10



WTISWT3626B12



WTISWT3626B14

**ELEVATION SYMBOL LEGEND:**



PANEL IS AVAILABLE AS FIXED ONLY



NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING

VALUES IN [ ] ARE MILLIMETER CONVERSIONS

VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**3-SASH TRANSOM UNITS**

M.O. Brickmould	90 15/16" [2310]	108 15/16" [2767]	96 15/16" [2462]
M.O. Adams/Flat Casing	94" [2388]	112" [2845]	100" [2540]
Rough Opening	88 9/16" [2249]	106 9/16" [2707]	94 9/16" [2402]
Frame Size	87 13/16" [2230]	105 13/16" [2688]	93 13/16" [2383]
Daylight Opening	18 5/8" [473] (3)	24 5/8" [625] (3)	20 5/8" [524] (3)

20 1/2" [521]  
22" [559] [476]  
18 3/4" [457]  
18" [457]  
10 15/16" [278]



WTISWR7616




WTISWR9016




WTISWT7616


32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTISWR7626



WTISWR9026



WTISWT7626

M.O. Brickmould	102 15/16" [2615]	114 15/16" [2919]
M.O. Adams/Flat Casing	106" [2692]	118" [2997]
Rough Opening	100 9/16" [2554]	112 9/16" [2859]
Frame Size	99 13/16" [2383]	111 13/16" [2840]
Daylight Opening	22 5/8" [575] (3)	26 5/8" [676] (3)

20 1/2" [521]  
22" [559] [476]  
18 3/4" [457]  
18" [457]  
10 15/16" [278]




WTISWT8016




WTISWT9016

32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTISWT8026



WTISWT9026

M.O. Brickmould	67 3/16" [1707]	71 3/16" [1808]	75 3/16" [1910]
M.O. Adams/Flat Casing	70 1/4" [1784]	74 1/4" [1886]	78 1/4" [1988]
Rough Opening	64 13/16" [1646]	68 13/16" [1748]	72 13/16" [1849]
Frame Size	64 1/16" [1627]	68 1/16" [1729]	72 1/16" [1830]
Daylight Opening	7 1/2" [190] (2)	9 1/2" [241] (2)	11 1/2" [292] (2)
	26 5/8" [676]	26 5/8" [676]	26 5/8" [676]


20 1/2" [521]  
22" [559] [476]  
18 3/4" [457]  
18" [457]  
10 15/16" [278]



WTISWT3016F10




WTISWT3016F12




WTISWT3016F14


32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTISWT3026F10



WTISWT3026F12



WTISWT3026F14

M.O. Brickmould	73 3/16" [1859]	77 3/16" [1961]	81 3/16" [2062]
M.O. Adams/Flat Casing	76 1/4" [1937]	80 1/4" [2038]	84 1/4" [2140]
Rough Opening	70 13/16" [1799]	74 13/16" [1900]	78 13/16" [2002]
Frame Size	70 1/16" [1780]	74 1/16" [1881]	78 1/16" [1963]
Daylight Opening	7 1/2" [190] (2)	9 1/2" [241] (2)	11 1/2" [292] (2)
	32 5/8" [829]	32 5/8" [829]	32 5/8" [829]

20 1/2" [521]  
22" [559] [476]  
18 3/4" [457]  
18" [457]  
10 15/16" [278]



WTISWT3616F10



WTISWT3616F12



WTISWT3616F14


32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTISWT3626F10



WTISWT3626F12



WTISWT3626F14

**ELEVATION SYMBOL LEGEND:**

**F** PANEL IS AVAILABLE AS FIXED ONLY

**##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**4-SASH TRANSOM UNITS**

M.O. Brickmould	96 1/8" [2442]	120 1/8" [3051]	144 1/8" [3661]
M.O. Adams/Flat Casing	99 3/16" [2519]	123 3/16" [3129]	147 3/16" [3739]
<b>Rough Opening</b>	<b>93 3/4" [2381]</b>	<b>117 3/4" [2991]</b>	<b>141 3/4" [3600]</b>
Frame Size	93" [2382]	117" [2972]	141" [3581]
Daylight Opening	12 5/8" [321] (4)	18 5/8" [473] (4)	24 5/8" [625] (4)

20 1/2" [521]  
22" [559]  
**18 3/4" [476]**  
18" [457]  
10 15/16" [278]



WTIFRR8016




WTIFRR10016




WTIFRR12016


32 1/2" [826]  
34" [864]  
**30 3/4" [781]**  
30" [762]  
22 15/16" [583]



WTIFRR8026



WTIFRR10026



WTIFRR12026

M.O. Brickmould	104 1/8" [2645]	128 1/8" [3254]	152 1/8" [3864]
M.O. Adams/Flat Casing	107 3/16" [2723]	131 3/16" [3332]	155 3/16" [3942]
<b>Rough Opening</b>	<b>101 3/4" [2584]</b>	<b>125 3/4" [3194]</b>	<b>149 3/4" [3804]</b>
Frame Size	101" [2565]	125" [3175]	149" [3785]
Daylight Opening	14 5/8" [371] (4)	20 5/8" [524] (4)	26 5/8" [676] (4)

20 1/2" [521]  
22" [559]  
**18 3/4" [476]**  
18" [457]  
10 15/16" [278]



WTIFRT8016




WTIFRT10016




WTIFRT10016


32 1/2" [826]  
34" [864]  
**30 3/4" [781]**  
30" [762]  
22 15/16" [583]



WTIFRT8026



WTIFRT10026



WTIFRT10026

**ELEVATION SYMBOL LEGEND:**



PANEL IS AVAILABLE AS FIXED ONLY



NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING

VALUES IN [ ] ARE MILLIMETER CONVERSIONS

VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**FRENCH DOOR W/2 SIDELITES**  
**TRANSOM**

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

92 3/8" [2346]  
95 7/16" [2424]  
90" [2286]  
89 1/4" [2267]  
7 1/2" [190] (2)  
20 5/8" [524] (2)

96 3/8" [2448]  
99 7/16" [2526]  
94" [2543]  
93 1/4" [2369]  
9 1/2" [241] (2)  
20 5/8" [524] (2)

100 3/8" [2550]  
103 7/16" [2627]  
98" [2489]  
97 1/4" [2470]  
11 1/2" [292] (2)  
20 5/8" [524] (2)

20 1/2" [521]  
22" [559]  
18 3/4" [476]  
18" [457]  
10 15/16" [278]



WTIFRT5016Q10



WTIFRT5016Q12



WTIFRT5016Q14

32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTIFRT5026Q10



WTIFRT5026Q12



WTIFRT5026Q14

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

96 3/8" [2448]  
99 7/16" [2526]  
94" [2388]  
93 1/4" [2369]  
7 1/2" [190] (2)  
22 5/8" [676] (2)


100 3/8" [2550]  
103 7/16" [2627]  
98" [2489]  
97 1/4" [2470]  
9 1/2" [241] (2)  
22 5/8" [676] (2)

104 3/8" [2651]  
107 7/16" [2769]  
102" [2591]  
101 1/4" [2572]  
11 1/2" [292] (2)  
22 5/8" [676] (2)

20 1/2" [521]  
22" [559]  
18 3/4" [476]  
18" [457]  
10 15/16" [278]



WTIFRT5416Q10



WTIFRT5416Q12



WTIFRT5416Q14

32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTIFRT5426Q10



WTIFRT5426Q12



WTIFRT5426Q14

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

104 3/8" [2651]  
107 7/16" [2729]  
101" [2591]  
101 1/4" [2572]  
27 1/2" [190] (2)  
26 5/8" [656] (2)

108 3/8" [2753]  
111 7/16" [2831]  
105" [2692]  
105 1/4" [2673]  
9 1/2" [241] (2)  
26 5/8" [656] (2)

112 3/8" [2854]  
115 7/16" [2932]  
109" [2794]  
109 1/4" [2775]  
11 1/2" [292] (2)  
26 5/8" [656] (2)

20 1/2" [521]  
22" [559]  
18 3/4" [476]  
18" [457]  
10 15/16" [278]



WTIFRT6016Q10



WTIFRT6016Q12



WTIFRT6016Q14

32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTIFRT6026Q10



WTIFRT6026Q12



WTIFRT6026Q14

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

116 3/8" [2956]  
119 7/16" [3034]  
114" [2896]  
113 1/4" [2877]  
7 1/2" [190] (2)  
32 5/8" [829] (2)

120 3/8" [3058]  
123 7/16" [3135]  
118" [2997]  
117 1/4" [2978]  
9 1/2" [241] (2)  
32 5/8" [829] (2)

124 3/8" [3159]  
127 7/16" [3237]  
122" [3099]  
121 1/4" [3080]  
11 1/2" [292] (2)  
32 5/8" [829] (2)

20 1/2" [521]  
22" [559]  
18 3/4" [476]  
18" [457]  
10 15/16" [278]



WTIFRT6016Q10



WTIFRT6016Q12



WTIFRT6016Q14

32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



WTIFRT6026Q10



WTIFRT6026Q12



WTIFRT6026Q14

**ELEVATION SYMBOL LEGEND:**

**(F)** PANEL IS AVAILABLE AS FIXED ONLY

**##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING

VALUES IN [ ] ARE MILLIMETER CONVERSIONS

VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**1- PANEL SECTOR TOP UNITS**

M.O. Brickmould	28 9/16" [725]	34 9/16" [878]	36 9/16" [929]	40 9/16" [1030]	46 9/16" [1183]
M.O. Adams/Flat Casing	31 5/8" [803]	37 5/8" [956]	39 5/8" [1006]	43 5/8" [1108]	49 5/8" [1260]
Rough Opening	26 3/16" [665]	32 3/16" [817]	34 3/16" [868]	38 3/16" [969]	44 3/16" [1122]
Frame Size	25 7/16" [646]	31 7/16" [799]	33 7/16" [849]	37 7/16" [951]	43 7/16" [1103]
Daylight Opening	14 5/8" [371]	20 5/8" [524]	22 5/8" [575]	26 5/8" [676]	32 5/8" [829]


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2086]  
68 11/16" [1745]



WISWTS2068




WISWTS2668



WISWTS2868



WISWTS3068



WISWTS3668


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WISWTS2070




WISWTS2670



WISWTS2870



WISWTS3070



WISWTS3670


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]




WISWTS2080




WISWTS2680



WISWTS2880



WISWTS3080



WISWTS3680


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WISWTS2090



WISWTS2690



WISWTS2890



WISWTS3090

**ELEVATION SYMBOL LEGEND:**

- (F)** PANEL IS AVAILABLE AS FIXED ONLY
- ##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.
- M.O.** = MASONRY OPENING
- VALUES IN [ ] ARE MILLIMETER CONVERSIONS
- VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**2- PANEL SECTOR TOP UNITS**

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

53 3/4" [1365]  
56 13/16" [1443]  
51 3/8" [1304]  
50 5/8" [1286]  
14 5/8" [371] (2)


65 3/4" [1670]  
68 13/16" [1748]  
63 3/8" [1610]  
62 5/8" [1591]  
20 5/8" [524] (2)

69 3/4" [1772]  
72 13/16" [1849]  
67 3/8" [1711]  
66 5/8" [1692]  
22 5/8" [575] (2)


77 3/4" [1975]  
80 13/16" [2053]  
75 3/8" [1914]  
74 5/8" [1895]  
26 5/8" [676] (2)

89 3/4" [2280]  
92 13/16" [2357]  
87 3/8" [2219]  
86 5/8" [2200]  
32 5/8" [829] (2)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2096]  
68 11/16" [1745]




WIFRTS4068




WIFRTS5068



WIFRTS5468




WIFRTS6068




WIFRTS7068


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]




WIFRTS4070




WIFRTS5070



WIFRTS5470




WIFRTS6070




WIFRTS7070


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]




WIFRTS4080




WIFRTS5080



WIFRTS5480



WIFRTS6080



WIFRTS7080

**ELEVATION SYMBOL LEGEND:**

- F** PANEL IS AVAILABLE AS FIXED ONLY
- ##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT


Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.




**ELEVATIONS**  
**2- PANEL SECTOR TOP UNITS**

M.O. Brickmould	53 3/4" [1365]	65 3/4" [1670]	69 3/4" [1772]	77 3/4" [1975]
M.O. Adams/Flat Casing	56 13/16" [1443]	68 13/16" [1748]	72 13/16" [1849]	80 13/16" [2053]
Rough Opening	51 3/8" [1304]	63 3/8" [1610]	67 3/8" [1711]	75 3/8" [1914]
Frame Size	50 5/8" [1286]	62 5/8" [1591]	66 5/8" [1692]	74 5/8" [1895]
Daylight Opening	14 5/8" [371] (2)	20 5/8" [524] (2)	22 5/8" [575] (2)	26 5/8" [676] (2)

100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]




WIFRTH5080




WIFRTH6080


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]




WIFRTS4090



WIFRTS5090




WIFRTS5490




WIFRTS6090

112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRTH5090



WIFRTH6090

**ELEVATION SYMBOL LEGEND:**

**(F)** PANEL IS AVAILABLE AS FIXED ONLY

**##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**3- PANEL SECTOR TOP UNITS**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

96 15/16" [2462]  
100" [2540]  
94 9/16" [2402]  
93 13/16" [2383]  
20 5/8" [524] (3)


102 15/16" [2615]  
106" [2692]  
100 9/16" [2554]  
99 13/16" [2535]  
22 5/8" [575] (3)

114 15/16" [2919]  
118" [2997]  
112 9/16" [2859]  
111 13/16" [2840]  
26 5/8" [676] (3)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2096]  
68 11/16" [1745]



WISWTS7668




WISWTS8068




WISWTS9068


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [22160]  
86 1/2" [2197]  
72 11/16" [1846]



WISWTS7670




WISWTS8070




WISWTS9070


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WISWTS7680




WISWTS8080




WISWTS9080


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WISWTS7690



WISWTS8090



WISWTS9090

**ELEVATION SYMBOL LEGEND:**  
F PANEL IS AVAILABLE AS FIXED ONLY

# NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.


**ELEVATIONS**  
**4-PANEL FRENCH DOOR SECTOR TOP UNITS**

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening


104 1/8" [2645]  
107 3/16" [2723]  
101 3/4" [2584]  
101" [2565]  
14 5/8" [371] (4)

128 1/8" [3254]  
131 3/16" [3332]  
125 3/4" [3194]  
125" [3175]  
20 5/8" [524] (4)

84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2068]  
68 11/16" [1745]




WIFRTS8068




WIFRTS10068

88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [22160]  
86 1/2" [2197]  
72 11/16" [1846]




WIFRTS8070




WIFRTS10070

100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]




WIFRTS8080




WIFRTS10080

112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRTS8090



WIFRTS10090

**ELEVATION SYMBOL LEGEND:**  
**F** PANEL IS AVAILABLE AS FIXED ONLY  
**#** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.  
 M.O. = MASONRY OPENING  
 VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
 VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**5'-0" WIDE FRENCH DOOR W/ 2 SIDELITES**  
**SECTOR TOP UNITS**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

92 3/8" [2346]  
95 7/16" [2424]  
90" [2286]  
89 1/4" [2267]  
7 1/2" [190] (2)  
20 5/8" [524] (2)


96 3/8" [2448]  
99 7/16" [2526]  
94" [2388]  
93 1/4" [2369]  
9 1/2" [241] (2)  
20 5/8" [524] (2)

100 3/8" [2550]  
103 7/16" [2627]  
98" [2489]  
97 1/4" [2470]  
11 1/2" [292] (2)  
20 5/8" [524] (2)


84 5/16" [2142]  
85 27/32" [2160]  
83 1/4" [2113]  
82 1/2" [2096]  
68 11/16" [1745]



WIFRTS5068Q10




WIFRTS5068Q12




WIFRTS5068Q14


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRTS5070Q10




WIFRTS5070Q12




WIFRTS5070Q14


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRTS5080Q10




WIFRTS5080Q12




WIFRTS5080Q14


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRTS5090Q10



WIFRTS5090Q12



WIFRTS5090Q14

**ELEVATION SYMBOL LEGEND:**

- (F) PANEL IS AVAILABLE AS FIXED ONLY
- ## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS  
5'-4" WIDE FRENCH SECTOR TOP DOORS  
W/ 2 SIDELITES**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

96 3/8" [2448]  
99 7/16" [2526]  
94" [2388]  
93 1/4" [2369]  
7 1/2" [190] (2)  
22 5/8" [575] (2)


100 3/8" [2550]  
103 7/16" [2627]  
98" [2489]  
97 1/4" [2470]  
9 1/2" [241] (2)  
22 5/8" [575] (2)

104 3/8" [2651]  
107 7/16" [2729]  
102" [2591]  
101 1/4" [2572]  
11 1/2" [292] (2)  
22 5/8" [575] (2)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2096]  
68 11/16" [1746]



WIFRTS5468Q10




WIFRTS5468Q12




WIFRTS5468Q14


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRTS5470Q10




WIFRTS5470Q12




WIFRTS5470Q14


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRTS5480Q10




WIFRTS5480Q12




WIFRTS5480Q14


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRTS5490Q10



WIFRTS5490Q12



WIFRTS5490Q14

**ELEVATION SYMBOL LEGEND:**  
ⓕ PANEL IS AVAILABLE AS FIXED ONLY

## NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**6'-0" FRENCH DOOR SECTOR TOP W/ 2**  
**SIDELITES**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

104 3/8" [2651]  
107 7/16" [2729]  
102" [2591]  
101 1/4" [2572]  
7 1/2" [190] (2)  
26 5/8" [676] (2)


108 3/8" [2753]  
111 7/16" [2831]  
106" [2692]  
105 1/4" [2673]  
9 1/2" [241] (2)  
26 5/8" [676] (2)

112 3/8" [2854]  
115 7/16" [2932]  
110" [2794]  
109 1/4" [2775]  
11 1/2" [292] (2)  
26 5/8" [676] (2)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2096]  
68 11/16" [1745]



WIFRTS6068Q10




WIFRTS6068Q12




WIFRTS6068Q14


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRTS6070Q10




WIFRTS6070Q12




WIFRTS6070Q14


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRTS6080Q10




WIFRTS6080Q12




WIFRTS6080Q14


112 5/16" [2853]  
113 27/32" [2892]  
111 1/4" [2826]  
110 1/2" [2807]  
96 11/16" [2456]



WIFRTS6090Q10



WIFRTS6090Q12



WIFRTS6090Q14

**ELEVATION SYMBOL LEGEND:**

- (F)** PANEL IS AVAILABLE AS FIXED ONLY
- ##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN [ ] ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**7'-0" WIDE FRENCH SECTOR TOP DOOR**  
**W/ 2 SIDELITES**


M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

116 3/8" [2956]  
119 7/16" [3034]  
114" [2896]  
113 1/4" [2877]  
7 1/2" [190] (2)  
32 5/8" [829] (2)


120 3/8" [3058]  
123 7/16" [3135]  
118" [2997]  
117 1/4" [2978]  
9 1/2" [241] (2)  
32 5/8" [829] (2)

124 3/8" [3159]  
127 7/16" [3237]  
122" [3099]  
121 1/4" [3080]  
11 1/2" [292] (2)  
32 5/8" [829] (2)


84 5/16" [2142]  
85 27/32" [2180]  
83 1/4" [2115]  
82 1/2" [2096]  
68 11/16" [1745]



WIFRTS7068Q10




WIFRTS7068Q12




WIFRTS7068Q14


88 5/16" [2243]  
89 27/32" [2282]  
87 1/4" [2216]  
86 1/2" [2197]  
72 11/16" [1846]



WIFRTS7070Q10




WIFRTS7070Q12




WIFRTS7070Q14


100 5/16" [2548]  
101 27/32" [2587]  
99 1/4" [2521]  
98 1/2" [2502]  
84 11/16" [2151]



WIFRTS7080Q10



WIFRTS7080Q12



WIFRTS7080Q14

- ELEVATION SYMBOL LEGEND:**
- (F)** PANEL IS AVAILABLE AS FIXED ONLY
  - ##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.
  - M.O.** = MASONRY OPENING
  - VALUES IN [ ] ARE MILLIMETER CONVERSIONS
  - VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.

**ELEVATIONS**  
**SECTOR TOP TRANSOM UNITS**

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

28 11/16" [729]  
31 3/4" [806]  
26 3/16" [665]  
25 7/16" [646]  
14 5/8" [371]

34 11/16" [881]  
37 3/4" [959]  
32 3/16" [818]  
31 7/16" [799]  
20 5/8" [524]

36 11/16" [932]  
39 3/4" [1010]  
34 3/16" [868]  
33 7/16" [849]  
22 5/8" [575]

40 11/16" [1033]  
43 3/4" [1111]  
38 3/16" [970]  
37 7/16" [951]  
26 5/8" [676]

22 1/2" [572]  
24" [607]  
20 3/4" [527]  
20" [508]  
12 15/16" [329]



CTISWTS2018



CTISWTS2618



CTISWTS2818



CTISWTS3018

32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



CTISWTS2026



CTISWTS2626



CTISWTS2826



CTISWTS3026

M.O. Brickmould  
M.O. Adams/Flat Casing  
Rough Opening  
Frame Size  
Daylight Opening

65 7/8" [1673]  
68 15/16" [1751]  
51 3/8" [1304]  
62 5/8" [1591]  
39 13/16" [1011]

65 7/8" [1673]  
68 15/16" [1751]  
63 3/8" [1610]  
62 5/8" [1591]  
51 13/16" [1316]

69 7/8" [1775]  
72 15/16" [1853]  
67 3/8" [1711]  
66 5/8" [1692]  
55 13/16" [1418]

77 7/8" [1978]  
80 15/16" [2056]  
75 3/8" [1914]  
74 5/8" [1895]  
63 13/16" [1621]

22 1/2" [572]  
24" [607]  
20 3/4" [527]  
20" [508]  
12 15/16" [329]



CTIFRTS4018



CTIFRTS5018



CTIFRTS5418



CTIFRTS6018

32 1/2" [826]  
34" [864]  
30 3/4" [781]  
30" [762]  
22 15/16" [583]



CTIFRTS4026



CTIFRTS5026



CTIFRTS5426



CTIFRTS6026

**ELEVATION SYMBOL LEGEND:**

- PANEL IS AVAILABLE AS FIXED ONLY
- ##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.

M.O. = MASONRY OPENING  
VALUES IN ( ) ARE MILLIMETER CONVERSIONS  
VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.



**ELEVATIONS**  
**VENTING SIDELITE UNITS**

	16 9/16" [421]	18 9/16" [471]	20 9/16" [522]	22 9/16" [573]	28 9/16" [725]	34 9/16" [878]	40 9/16" [1029]
UNIT SIZE	16 9/16" [421]	18 9/16" [471]	20 9/16" [522]	22 9/16" [573]	28 9/16" [725]	34 9/16" [878]	40 9/16" [1029]
ROUGH OPENING	14 5/16" [364]	16 5/16" [414]	18 5/16" [465]	20 5/16" [516]	26 5/16" [668]	32 5/16" [821]	38 5/16" [973]
FRAME SIZE	13 9/16" [344]	15 9/16" [395]	17 9/16" [446]	19 9/16" [497]	25 9/16" [649]	31 9/16" [802]	37 9/16" [954]
DAYLIGHT OPENING	2 11/16" [69] (2)	4 11/16" [121] (2)	6 11/16" [172] (2)	8 11/16" [222] (2)	14 11/16" [375] (2)	20 11/16" [527] (2)	26 11/16" [680] (2)
85 1/2" [2172]							
83 1/4" [2115]							
82 1/2" [2096]							
68 11/16" [1746]							
89 1/2" [2273]							
87 1/4" [2216]							
86 1/2" [2198]							
72 11/16" [1848]							
101 1/2" [2571]							
99 1/4" [2521]							
98 1/2" [2502]							
84 11/16" [2152]							
113 1/2" [3037]							
111 1/4" [2826]							
110 1/2" [2807]							
96 11/16" [2457]							
125 1/2" [3818]							
123 1/4" [3131]							
122 1/2" [3112]							
108 11/16" [2762]							

**ELEVATION SYMBOL LEGEND:**

- (F)** PANEL IS AVAILABLE AS FIXED ONLY
- ##** NUMBER INDICATES DESIGN PRESSURE (DP) RATING WITH STANDARD GLAZING.
- M.O.** = MASONRY OPENING
- VALUES IN [ ] ARE MILLIMETER CONVERSIONS
- VALUES IN ( ) ARE NUMBER OF DAYLIGHT OPENINGS PER UNIT

Note: Elevations shown DO NOT have exterior trim. Subtract 1/2" [12.7] from M.O. (Masonry Opening) for Unit Size. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Openings & Masonry Openings page.