
ELEVATIONS TABLE OF CONTENTS

Operating Units.	1-20
Fixed Units.	1-26

OPERATING UNIT ELEVATIONS

M.O. BRICKMOULD	21 1/4" (540)	23 1/4" (591)	27 1/4" (692)	31 1/4" (794)	33 1/4" (845)	35 1/4" (895)	39 1/4" (997)
M.O. ADAMS/FLAT CASING	24 5/16" (618)	26 5/16" (668)	30 5/16" (770)	34 5/16" (872)	36 5/16" (922)	38 5/16" (973)	42 5/16" (1075)
ROUGH OPENING	18 3/4" (476)	20 3/4" (527)	24 3/4" (629)	28 3/4" (730)	30 3/4" (781)	32 3/4" (832)	36 3/4" (933)
FRAME SIZE	18" (457)	20" (508)	24" (610)	28" (711)	30" (762)	32" (813)	36" (914)
DAYLIGHT OPENING	11 7/8" (302)	13 7/8" (352)	17 7/8" (454)	21 7/8" (556)	23 7/8" (606)	25 7/8" (657)	29 7/8" (759)
17 1/4" (438) 18 11/16" (475) 14 3/4" (375) 14" (356) 7 7/8" (200)							
21 1/4" (540) 22 11/16" (576) 18 3/4" (476) 18" (457) 11 7/8" (302)							
23 1/4" (591) 24 11/16" (627) 20 3/4" (527) 20" (508) 13 7/8" (352)							
27 1/4" (692) 28 11/16" (729) 24 3/4" (629) 24" (610) 17 7/8" (454)							
31 1/4" (794) 32 11/16" (830) 28 3/4" (730) 28" (711) 21 7/8" (556)							
33 1/4" (845) 34 11/16" (881) 30 3/4" (781) 30" (762) 23 7/8" (606)							
35 1/4" (895) 36 11/16" (932) 32 3/4" (832) 32" (813) 25 7/8" (657)							
39 1/4" (997) 40 11/16" (1033) 36 3/4" (933) 36" (914) 29 7/8" (759)							

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PREFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING UNIT ELEVATIONS

	21 1/4" (540)	23 1/4" (591)	27 1/4" (692)	31 1/4" (794)	33 1/4" (845)	35 1/4" (895)	39 1/4" (997)
M.O. BRICKMOUND	24 5/16" (618)	26 5/16" (668)	30 5/16" (770)	34 5/16" (872)	36 5/16" (922)	38 5/16" (973)	42 5/16" (1075)
M.O. ADAMS/FLAT CASING	18 3/4" (476)	20 3/4" (527)	24 3/4" (629)	28 3/4" (730)	30 3/4" (781)	32 3/4" (832)	36 3/4" (933)
ROUGH OPENING	18" (457)	20" (508)	24" (610)	28" (711)	30" (762)	32" (813)	36" (914)
FRAME SIZE	11 7/8" (302)	13 7/8" (352)	17 7/8" (454)	21 7/8" (556)	23 7/8" (606)	25 7/8" (657)	29 7/8" (759)
DAYLIGHT OPENING							
	CWPOA1840	CWPOA2040	CWPOA2440	CWPOA2840	CWPOA3040	CWPOA3240	CWPOA3640
	CWPOA1842	CWPOA2042	CWPOA2442	CWPOA2842	CWPOA3042	CWPOA3242	CWPOA3642
	CWPOA1848	CWPOA2048	CWPOA2448	CWPOA2848	CWPOA3048	CWPOA3248	CWPOA3648

43 1/4" (1089)
44 11/16" (1135)
40 3/4" (1035)
40" (1016)
33 7/8" (860)

45 1/4" (1149)
46 11/16" (1186)
42 3/4" (1086)
42" (1067)
35 7/8" (911)

51 1/4" (1302)
52 11/16" (1338)
48 3/4" (1238)
48" (1219)
41 7/8" (1064)

ELEVATION SYMBOL LEGEND:
M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PREFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING UNIT ELEVATIONS

M.O. BRICKMOULD	43 1/4" (1099)	45 1/4" (1149)	51 1/4" (1302)	57 1/4" (1454)	59 1/4" (1505)
M.O. ADAMS/FLAT CASING	46 5/16" (1176)	48 5/16" (1227)	54 5/16" (1380)	60 5/16" (1532)	62 5/16" (1583)
ROUGH OPENING	40 3/4" (1035)	42 3/4" (1086)	48 3/4" (1238)	54 3/4" (1391)	56 3/4" (1441)
FRAME SIZE	40" (1016)	42" (1067)	48" (1219)	54" (1372)	56" (1422)
DAYLIGHT OPENING	33 7/8" (860)	35 7/8" (911)	41 7/8" (1064)	47 7/8" (1216)	49 7/8" (1267)
17 1/4" (438) 18 1/16" (475) 14 3/4" (375) 14" (356) 7 7/8" (200)					
21 1/4" (540) 22 1/16" (576) 18 3/4" (476) 18" (457) 11 7/8" (302)					
23 1/4" (591) 24 1/16" (627) 20 3/4" (527) 20" (508) 13 7/8" (352)					
27 1/4" (692) 28 1/16" (729) 24 3/4" (629) 24" (610) 17 7/8" (454)					
31 1/4" (794) 32 1/16" (830) 28 3/4" (730) 28" (711) 21 7/8" (556)					
33 1/4" (845) 34 1/16" (881) 30 3/4" (781) 30" (762) 23 7/8" (606)					
35 1/4" (895) 36 1/16" (932) 32 3/4" (832) 32" (813) 25 7/8" (657)					
39 1/4" (997) 40 1/16" (1033) 36 3/4" (933) 36" (914) 29 7/8" (759)					

ELEVATION SYMBOL LEGEND:

M.O. = MASONRY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING UNIT ELEVATIONS

	43 1/4" (1099)	45 1/4" (1149)	51 1/4" (1302)	57 1/4" (1454)	59 1/4" (1505)
M.O. BRICKMOULD	46 5/16" (1176)	48 5/16" (1227)	54 5/16" (1380)	60 5/16" (1532)	62 5/16" (1583)
M.O. ADAMS/FLAT CASING	40 3/4" (1035)	42 3/4" (1086)	48 3/4" (1238)	54 3/4" (1391)	56 3/4" (1441)
ROUGH OPENING	40" (1016)	42" (1067)	48" (1219)	54" (1372)	56" (1422)
FRAME SIZE	33 7/8" (860)	35 7/8" (911)	41 7/8" (1064)	47 7/8" (1216)	49 7/8" (1267)
DAYLIGHT OPENING					
	CWPOA4040	CWPOA4240	CWPOA4840	CWPOA5440	CWPOA5640
	CWPOA4042	CWPOA4242	CWPOA4842	CWPOA5442	CWPOA5642
	CWPOA4048	CWPOA4248	CWPOA4848	CWPOA5448	CWPOA5648

43 1/4" (1099)
44 11/16" (1135)
40 3/4" (1035)
40" (1016)
33 7/8" (860)

45 1/4" (1149)
46 11/16" (1186)
42 3/4" (1086)
42" (1067)
35 7/8" (911)

51 1/4" (1302)
52 11/16" (1338)
48 3/4" (1238)
48" (1219)
41 7/8" (1064)

ELEVATION SYMBOL LEGEND:
M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PREFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING UNIT ELEVATIONS

M.O. BRICKMOUND
M.O. ADAMS/FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

63 1/4" (1607)
66 5/16" (1684)
60 3/4" (1543)
60"(1524)
53 7/8" (1368)

69 1/4" (1759)
72 5/16" (1837)
66 3/4" (1695)
66"(1676)
59 7/8" (1521)

75 1/4" (1911)
78 5/16" (1989)
72 3/4" (1848)
72"(1829)
65 7/8" (1673)

17 1/4" (438)
18 11/16" (475)
14 3/4"(375)
14"(356)
7 7/8"(200)



CWPOA6014



CWPOA6614



CWPOA7214

21 1/4" (540)
22 11/16" (576)
18 3/4"(476)
18"(457)
11 7/8" (302)



CWPOA6018




CWPOA6618




CWPOA7218

23 1/4" (591)
24 11/16" (627)
20 3/4" (527)
20"(508)
13 7/8" (352)



CWPOA6020



CWPOA6620



CWPOA7220

27 1/4" (682)
28 11/16" (729)
24 3/4" (629)
24"(610)
17 7/8" (454)



CWPOA6024



CWPOA6624




CWPOA7224

31 1/4" (794)
32 11/16" (830)
28 3/4" (730)
28"(711)
21 7/8" (556)



CWPOA6028



CWPOA6628



CWPOA7228

33 1/4" (845)
34 11/16" (881)
30 3/4" (781)
30"(762)
23 7/8" (606)



CWPOA6030




CWPOA6630




CWPOA7230


35 1/4" (895)
36 11/16" (932)
32 3/4" (832)
32"(813)
25 7/8" (657)



CWPOA6032



CWPOA6632



CWPOA7232

39 1/4" (997)
40 11/16" (1033)
36 3/4" (933)
36"(914)
29 7/8" (759)



CWPOA6036



CWPOA6636



CWPOA7236

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

OPERATING UNIT ELEVATIONS

M.O. BRICKMOUND
M.O. ADAMS/FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

63 1/4" (1607)
66 5/16" (1684)
60 3/4" (1543)
60"(1524)
53 7/8" (1368)

69 1/4" (1759)
72 5/16" (1837)
66 3/4" (1695)
66"(1676)
59 7/8" (1521)

75 1/4" (1911)
78 5/16" (1989)
72 3/4" (1848)
72"(1829)
65 7/8" (1673)

43 1/4" (1099)
44 11/16" (1135)
40 3/4" (1035)
40"(1016)
33 7/8" (860)



CWPOA6040




CWPOA6640



CWPOA7240


45 1/4" (1149)
46 11/16" (1186)
42 3/4" (1086)
42"(1067)
35 7/8" (911)



CWPOA6042




CWPOA6642




CWPOA7242


51 1/4" (1302)
52 11/16" (1338)
48 3/4" (1238)
48"(1219)
41 7/8" (1064)



CWPOA6048



CWPOA6648



CWPOA7248

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PREFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

M.O. BRICKMOULD	21 1/4" (540)	23 1/4" (591)	27 1/4" (692)	31 1/4" (794)	33 1/4" (845)	35 1/4" (895)	39 1/4" (997)
M.O. ADAMS/FLAT CASING	24 5/16" (618)	26 5/16" (668)	30 5/16" (770)	34 5/16" (872)	36 5/16" (922)	38 5/16" (973)	42 5/16" (1075)
ROUGH OPENING	18 3/4" (476)	20 3/4" (527)	24 3/4" (629)	28 3/4" (730)	30 3/4" (781)	32 3/4" (832)	36 3/4" (933)
FRAME SIZE	18" (457)	20" (508)	24" (610)	28" (711)	30" (762)	32" (813)	36" (914)
DAYLIGHT OPENING	11 7/8" (302)	13 7/8" (352)	17 7/8" (454)	21 7/8" (556)	23 7/8" (606)	25 7/8" (657)	29 7/8" (759)
17 1/4" (438) 18 11/16" (475) 14 3/4" (375) 14" (356) 7 7/8" (200)							
21 1/4" (540) 22 11/16" (576) 18 3/4" (476) 18" (457) 11 7/8" (302)							
23 1/4" (591) 24 11/16" (627) 20 3/4" (527) 20" (508) 13 7/8" (352)							
27 1/4" (692) 28 11/16" (729) 24 3/4" (629) 24" (610) 17 7/8" (454)							
31 1/4" (794) 32 11/16" (830) 28 3/4" (730) 28" (711) 21 7/8" (556)							
33 1/4" (845) 34 11/16" (881) 30 3/4" (781) 30" (762) 23 7/8" (606)							
35 1/4" (895) 36 11/16" (932) 32 3/4" (832) 32" (813) 25 7/8" (657)							
39 1/4" (997) 40 11/16" (1033) 36 3/4" (933) 36" (914) 29 7/8" (759)							

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PREFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

	21 1/4" (540)	23 1/4" (591)	27 1/4" (692)	31 1/4" (794)	33 1/4" (845)	35 1/4" (895)	39 1/4" (997)
M.O. BRICKMOUND	24 5/16" (618)	26 5/16" (668)	30 5/16" (770)	34 5/16" (872)	36 5/16" (922)	38 5/16" (973)	42 5/16" (1075)
M.O. ADAMS/FLAT CASING	18 3/4" (476)	20 3/4" (527)	24 3/4" (629)	28 3/4" (730)	30 3/4" (781)	32 3/4" (832)	36 3/4" (933)
ROUGH OPENING	18" (457)	20" (508)	24" (610)	28" (711)	30" (762)	32" (813)	36" (914)
FRAME SIZE	11 7/8" (302)	13 7/8" (352)	17 7/8" (454)	21 7/8" (556)	23 7/8" (606)	25 7/8" (657)	29 7/8" (759)
DAYLIGHT OPENING							
	CWPOA1840	CWPOA2040	CWPOA2440	CWPOA2840	CWPOA3040	CWPOA3240	CWPOA3640
	CWPOA1842	CWPOA2042	CWPOA2442	CWPOA2842	CWPOA3042	CWPOA3242	CWPOA3642
	CWPOA1848	CWPOA2048	CWPOA2448	CWPOA2848	CWPOA3048	CWPOA3248	CWPOA3648

43 1/4" (1089)
44 11/16" (1135)
40 3/4" (1035)
40" (1016)
33 7/8" (860)

45 1/4" (1149)
46 11/16" (1186)
42 3/4" (1086)
42" (1067)
35 7/8" (911)

51 1/4" (1302)
52 11/16" (1338)
48 3/4" (1238)
48" (1219)
41 7/8" (1064)

ELEVATION SYMBOL LEGEND:
M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PREFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

M.O. BRICKMOULD	43 1/4" (1099)	45 1/4" (1149)	51 1/4" (1302)	57 1/4" (1454)	59 1/4" (1505)
M.O. ADAMS/FLAT CASING	46 5/16" (1176)	48 5/16" (1227)	54 5/16" (1380)	60 5/16" (1532)	62 5/16" (1583)
ROUGH OPENING	40 3/4" (1035)	42 3/4" (1086)	48 3/4" (1238)	54 3/4" (1391)	56 3/4" (1441)
FRAME SIZE	40" (1016)	42" (1067)	48" (1219)	54" (1372)	56" (1422)
DAYLIGHT OPENING	33 7/8" (860)	35 7/8" (911)	41 7/8" (1064)	47 7/8" (1216)	49 7/8" (1267)
17 1/4" (438) 18 11/16" (475) 14 3/4" (375) 14" (356) 7 7/8" (200)					
21 1/4" (540) 22 11/16" (576) 18 3/4" (476) 18" (457) 11 7/8" (302)					
23 1/4" (591) 24 11/16" (627) 20 3/4" (527) 20" (508) 13 7/8" (352)					
27 1/4" (692) 28 11/16" (729) 24 3/4" (629) 24" (610) 17 7/8" (454)					
31 1/4" (794) 32 11/16" (830) 28 3/4" (730) 28" (711) 21 7/8" (556)					
33 1/4" (845) 34 11/16" (881) 30 3/4" (781) 30" (762) 23 7/8" (606)					
35 1/4" (895) 36 11/16" (932) 32 3/4" (832) 32" (813) 25 7/8" (657)					
39 1/4" (997) 40 11/16" (1033) 36 3/4" (933) 36" (914) 29 7/8" (759)					

ELEVATION SYMBOL LEGEND:

M.O. = MASONRY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

M.O. BRICKMOULD
M.O. ADAMS/FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

43 1/4" (1099)
46 5/16" (1176)
40 3/4" (1035)
40"(1016)
33 7/8" (860)


45 1/4" (1149)
48 5/16" (1227)
42 3/4" (1086)
42"(1067)
35 7/8" (911)

51 1/4" (1302)
54 5/16" (1380)
48 3/4" (1238)
48"(1219)
41 7/8" (1064)


57 1/4" (1454)
60 5/16" (1532)
54 3/4" (1391)
54"(1372)
47 7/8" (1216)

59 1/4" (1505)
62 5/16" (1583)
56 3/4" (1441)
56"(1422)
49 7/8" (1267)


43 1/4" (1099)
44 11/16" (1135)
40 3/4" (1035)
40"(1016)
33 7/8" (860)




CWPOA4040



CWPOA4240



CWPOA4840




CWPOA5440




CWPOA5640


45 1/4" (1149)
46 11/16" (1186)
42 3/4" (1086)
42"(1067)
35 7/8" (911)




CWPOA4042




CWPOA4242



CWPOA4842




CWPOA5442




CWPOA5642


51 1/4" (1302)
52 11/16" (1338)
48 3/4" (1238)
48"(1219)
41 7/8" (1064)




CWPOA4048




CWPOA4248



CWPOA4848



CWPOA5448



CWPOA5648

ELEVATION SYMBOL LEGEND:
M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PREFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

M.O. BRICKMOUND
M.O. ADAMS/FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

63 1/4" (1607)
66 5/16" (1684)
60 3/4" (1543)
60"(1524)
53 7/8" (1368)

69 1/4" (1759)
72 5/16" (1837)
66 3/4" (1695)
66"(1676)
59 7/8" (1521)

75 1/4" (1911)
78 5/16" (1989)
72 3/4" (1848)
72"(1829)
65 7/8" (1673)

17 1/4" (438)
18 11/16" (475)
14 3/4" (375)
14"(366)
7 7/8" (200)



CWPOA6014



CWPOA6614



CWPOA7214

21 1/4" (540)
22 11/16" (576)
18 3/4" (476)
18"(457)
11 7/8" (302)



CWPOA6018



CWPOA6618



CWPOA7218

23 1/4" (591)
24 11/16" (627)
20 3/4" (527)
20"(508)
13 7/8" (352)



CWPOA6020



CWPOA6620



CWPOA7220

27 1/4" (682)
28 11/16" (729)
24 3/4" (629)
24"(610)
17 7/8" (454)



CWPOA6024



CWPOA6624



CWPOA7224

31 1/4" (794)
32 11/16" (830)
28 3/4" (730)
28"(711)
21 7/8" (556)



CWPOA6028




CWPOA6628




CWPOA7228


33 1/4" (845)
34 11/16" (881)
30 3/4" (781)
30"(762)
23 7/8" (606)



CWPOA6030



CWPOA6630



CWPOA7230

35 1/4" (895)
36 11/16" (932)
32 3/4" (832)
32"(813)
25 7/8" (657)



CWPOA6032



CWPOA6632



CWPOA7232

39 1/4" (997)
40 11/16" (1033)
36 3/4" (933)
36"(914)
29 7/8" (759)



CWPOA6036



CWPOA6636



CWPOA7236

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PERFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.

FIXED UNIT ELEVATIONS

M.O. BRICKMOULD
M.O. ADAMS/FLAT CASING
ROUGH OPENING
FRAME SIZE
DAYLIGHT OPENING

63 1/4" (1607)
66 5/16" (1684)
60 3/4" (1543)
60"(1524)
53 7/8" (1368)

69 1/4" (1759)
72 5/16" (1837)
66 3/4" (1695)
66"(1676)
59 7/8" (1521)

75 1/4" (1911)
78 5/16" (1989)
72 3/4" (1848)
72"(1829)
65 7/8" (1673)

43 1/4" (1099)
44 11/16" (1135)
40 3/4" (1035)
40"(1016)
33 7/8" (860)



CWPOA6040



CWPOA6640




CWPOA7240


45 1/4" (1149)
46 11/16" (1186)
42 3/4" (1086)
42"(1067)
35 7/8" (911)



CWPOA6042




CWPOA6642




CWPOA7242


51 1/4" (1302)
52 11/16" (1338)
48 3/4" (1238)
48"(1219)
41 7/8" (1064)



CWPOA6048



CWPOA6648



CWPOA7248

ELEVATION SYMBOL LEGEND:

M.O. = MASORNY OPENING
VALUES IN () ARE IN MILLIMETER CONVERSIONS
NUMBER INDICATES PREFORMANCE GRADE (PG) RATING WITH STANDARD GLAZING

Note: Elevations shown DO NOT have exterior trim. Subtract 3/4"(19) from M.O.(Masonry Opening) for Unit Sizes. Masonry openings above include Sill Nose, see Trim Options page for Sill Nose specifications. For other Trim Options refer to the Unit Sizing, Rough Opening & Masonry Openings page.